

Product Technical Sheet

12 Aug 2021 14:40



569.63863

INTERLOCKED SOCKET

63A 3P+E 12h TST>50V 50Hz 60Hz
136X390MM_HD Screw terminals With
mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE 2 HD Series	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements
Type of product	INTERLOCKED SOCKET	CEI EN 60309-2 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	63A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	3P+E		
Hour position	12h		
Rated voltage (range)	200-250V		
Rated voltage	TST>50V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Flange	136X390MM_HD
Cable entry	DRILLING POINT MARK
Options	With mechanical interlock
Notes	WITH DIN RAIL (6 MODULES)
Padlock	ø5mm