Product Technical Sheet

12 Aug 2021 14:52





452.16663 FLUSH-MOUNTING SOCKET

16A 3P+E 12h TST>50V 50Hz 60Hz 70X87MM Screw terminals

Product Approvals

| TEOUDATA | | OTANDADDO | AND LAWO |
|----------------------------|---------------------------|---|---|
| TECHDATA | | STANDARDS | AND LAWS |
| Commercial series | EUREKA Series | CEI EN 60309-1 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part |
| Type of product | FLUSH-MOUNTING SOCKET | CEI EN 60309-2 [Italian Standa (1992) and couplers f | General requirements [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part |
| Synthetical description | FLUSH-MOUNTING SOCKET | | 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Mounting version | FLUSH/SURFACE MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 16A | | |
| Poles | 3P+E | | |
| Hour position | 12h | | |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | TST>50V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK07 | | |
| Types of available outlets | 90° ANGLED | | |
| | | | |

| Terminals | Screw terminals |
|------------------|-----------------|
| Contact material | CuZn (brass) |
| Flange | 70X87MM |
| Cable entry | PG 16 |