



545.16874

INTERLOCKED SOCKET

16A 3P+N+E 3h 380V 50Hz / 440V 60Hz 50Hz
60Hz Screw terminals With mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	3P+N+E		
Hour position	3h		
Rated voltage (range)	250-400V		
Rated voltage	380V 50Hz / 440V 60Hz		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Cable entry	PG 21
Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER