Product Technical Sheet

12 Aug 2021 14:58





552.16877INTERLOCKED SOCKET

16A 3P+N+E 5h 600-690V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Type of product	INTERLOCKED SOCKET	and couplers for industrial purposes. Par 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configuration	[European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING		
Rated current	16A	DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive /UE	
Poles	3P+N+E		
Hour position	5h		
Rated voltage (range)	400-up		
Rated voltage	600-690V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLACK		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Cable entry	PG 21
Options	With mechanical interlock
Notes	WITH DIN RAIL (4 MODULES)