

Product Technical Sheet

12 Aug 2021 15:03



564.16863

INTERLOCKED SOCKET

16A 3P+E 12h TST>50V 50Hz 60Hz
106X240MM_HD Screw terminals With
mechanical interlock

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|--|
| Commercial series | ADVANCE 2 HD Series | CEI EN 60309-1 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements |
| Type of product | INTERLOCKED SOCKET | CEI EN 60309-2 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 16A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Poles | 3P+E | | |
| Hour position | 12h | | |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | TST>50V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK08 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |

| | |
|-------------|---------------------------|
| Flange | 106X240MM_HD |
| Cable entry | M25X1,5 |
| Options | With mechanical interlock |
| Notes | WITH FUSE HOLDER |
| Padlock | ø5mm |