



161.40501.F

MULTI SOCKET

2P+E-16A-(S17) TRANS. TINTED 4x2P+E-16A-(P40)

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------------|---------------------|-----------------------------------|--|
| Type of product | MULTI SOCKET | CEI 23-124 (2012-08) | [Italian Standard] Spine e prese per usi domestici e similari - Parte 2-7: Prescrizioni particolari per cordoni prolungatori |
| Commercial series | SICURA Series | CEI 23-124 V1 (2015-01) | [Italian Standard] Spine e prese per usi domestici e similari - Parte 2-7: Prescrizioni particolari per cordoni prolungatori |
| Synthetical description | MULTI SOCKET | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 16A | DIRECTIVE RoHS 2011/65/EU | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment |
| Poles | 2P+E | | |
| Rated voltage | 250V | | |
| Type of plugs | 2P+E-16A-(S17) | | |
| Abbreviation of individuation | P40 | | |
| No. of available outlets | 4 NR | | |
| Type of sockets | 4x2P+E-16A-(P40) | | |
| Cable length | 1,5m | | |
| Cable | H05VV-F | | |
| Cable section | 1mm ² | | |
| Max power | MAX 3.600W | | |
| Material | ENGINEERING PLASTIC | | |
| Colour | TRANS. TINTED | | |
| Options | With cable and plug | | |