



590.JGE2005 SWITCH DISCONNECTOR

20A 3P+N IP66 115x190x128mm Y1 IK10
GENERAL GREY/BLACK GW 960°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-HD Series	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP66	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	GREY/BLACK	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	20A		
Poles	3P+N		
Switch size	Y1		
Rated voltage	690V		
Dimensions	115x190x128mm		
GLOW WIRE	GW 960°C		
Protection degree IK	IK10		
Ambient temperature Ta min	-40 °C		
Ambient temperature Ta max	60 °C		