

xcore


3 YEARS WARRANTY



Standards: EN 60598-1:2015, EN 60598-2-1:1989, EN 62493:2015, EN 62471:2008, EN 62031:2008 + A2:2015, EN 60529:1992 + A2:2013, EN 55015:2013 + A1:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61547:2009

FINISHING AVAILABLE

MWH MBK



EN

Round or square ceiling light fittings for interior, surface mounted, equipped with COB LEDs. Structure of die-cast aluminum, electrostatically painted.

Optical system with FRESNEL lens of polycarbonate, UGR<10. Constant current LED driver included.

Range of applications

General interior lighting, decorative lighting.

RO

Plafoniere rotunde sau pătrate, de interior, pentru montaj aparent, echipate cu LED-uri COB. Structură din aluminiu turnat, vopsită în câmp electrostatic.

Sistem optic cu lentilă FRESNEL din policarbonat. Alimentator LED în curent constant inclus, UGR<10.

Aplicații

Iluminatul general de interior, iluminatul decorativ.

IT

Plafoniere tonde o quadrate per interni, montaggio da superficie, equipaggiate con LED COB. Struttura in pressofusione di alluminio, verniciato a polveri.

Sistema ottico con lente FRESNEL in policarbonato, UGR<10.



Alimentatore LED in corrente costante incluso.

Campi di applicazione

Illuminazione generale d'interni, illuminazione decorativa.

XCORE ROUND



CRR01 CRR02



Code	Finishing	Type of LED	Power	Input voltage	Output current /voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
CRR01UWW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	755 lm	467 lm	2700K	80	38°	0,25 kg
CRR01WW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	780 lm	482 lm	3000K	80	38°	0,25 kg
CRR01NW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	840 lm	514 lm	4000K	80	38°	0,25 kg
CRR01UWW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	755 lm	467 lm	2700K	80	38°	0,25 kg
CRR01WW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	780 lm	482 lm	3000K	80	38°	0,25 kg
CRR01NW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	840 lm	514 lm	4000K	80	38°	0,25 kg
CRR02UWW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2030 lm	1362 lm	2700K	80	38°	0,52 kg
CRR02WW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2100 lm	1397 lm	3000K	80	38°	0,52 kg
CRR02NW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2260 lm	1489 lm	4000K	80	38°	0,52 kg
CRR02UWW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2030 lm	1362 lm	2700K	80	38°	0,52 kg
CRR02WW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2100 lm	1397 lm	3000K	80	38°	0,52 kg
CRR02NW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2260 lm	1489 lm	4000K	80	38°	0,52 kg

XCORE SQUARE

CRQ01 CRQ02



Code	Finishing	Type of LED	Power	Input voltage	Output current /voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
CRQ01UWW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	755 lm	467 lm	2700K	80	38°	0,19 kg
CRQ01WW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	780 lm	479 lm	3000K	80	38°	0,19 kg
CRQ01NW MWH	MWH	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	840 lm	512 lm	4000K	80	38°	0,19 kg
CRQ01UWW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	755 lm	467 lm	2700K	80	38°	0,19 kg
CRQ01WW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	780 lm	479 lm	3000K	80	38°	0,19 kg
CRQ01NW MBK	MBK	COB CREE	6W	220-240V AC	650 mA / 9V DC	Included	840 lm	512 lm	4000K	80	38°	0,19 kg
CRQ02UWW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2030 lm	1362 lm	2700K	80	38°	0,56 kg
CRQ02WW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2100 lm	1395 lm	3000K	80	38°	0,56 kg
CRQ02NW MWH	MWH	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2260 lm	1487 lm	4000K	80	38°	0,56 kg
CRQ02UWW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2030 lm	1362 lm	2700K	80	38°	0,56 kg
CRQ02WW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2100 lm	1395 lm	3000K	80	38°	0,56 kg
CRQ02NW MBK	MBK	COB CREE	18W	220-240V AC	450 mA / 36V DC	Included	2260 lm	1487 lm	4000K	80	38°	0,56 kg