

xargo

3 YEARS
WARRANTY



EN

Recessed light fittings for interior, adjustable, equipped with COB LEDs.

Recessed frame, mobile element and heat sink of die-cast aluminum, electrostatically painted.

Reflector of silver faceted polycarbonate.

Diffuser of transparent polycarbonate, optical system UGR<16.

Black painted circular decorative element of aluminum. Constant current LED driver delivered with the light fitting.

Range of applications

General or accent lighting in commercial areas, museums and other exhibition spaces, residential and recreational areas. Domestic lighting.

RO

Corpur de iluminat orientabile încastrate, de interior, echipate cu LED-uri COB.

Rama de încastrare, elementul mobil și radiatorul din aluminiu turnat, vopsite în câmp electrostatic.

Reflector din policarbonat argintat și fațetat.

Dispensor din policarbonat transparent, sistem optic UGR<16.

Element decorativ circular din aluminiu vopsit negru.

Alimentator în curent constant livrat împreună cu corpul de iluminat.

Aplicații

Iluminatul general sau de accent în spații comerciale, muzee și alte spații de expunere, zone rezidențiale și zone de agrement. Iluminatul domestic.

IT

Apparecchi orientabili da incasso per interni, equipaggiati con LED COB.

Cornice da incasso, elemento mobile e raffreddatore in pressofusione di alluminio verniciati a polveri.

Riflettore in policarbonato argentato e sfaccettato.


Diffusore in policarbonato trasparente, sistema ottico UGR<16.

Elemento decorativo circolare in alluminio verniciato nero opaco.

Alimentatore in corrente costante fornito con l'apparecchio.


Campi di applicazione

Iluminazione generale o d'accento in musei, spazi espositivi, aree residenziali e ricreative. Illuminazione domestica.



AGR01


FINISHING AVAILABLE



Code	Finishing	LED type	Power	Input voltage	Output current /voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Ø	Weight
AGR01UWW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	930 lm	741 lm	2700K	90	38°	Ø84 mm	0,39 kg
AGR01WW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	960 lm	762 lm	3000K	90	38°	Ø84 mm	0,39 kg
AGR01NW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	1120 lm	812 lm	4000K	90	38°	Ø84 mm	0,39 kg
AGR01UWW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	930 lm	741 lm	2700K	90	38°	Ø84 mm	0,39 kg
AGR01WW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	960 lm	762 lm	3000K	90	38°	Ø84 mm	0,39 kg
AGR01NW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	1120 lm	812 lm	4000K	90	38°	Ø84 mm	0,39 kg

AGR02


FINISHING AVAILABLE



Code	Finishing	LED type	Power	Input voltage	Output current /voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Ø	Weight
AGR02UWW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	930 lm	741 lm	2700K	90	38°	84x84 mm	0,40 kg
AGR02WW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	960 lm	762 lm	3000K	90	38°	84x84 mm	0,40 kg
AGR02NW MWH/BK	MWH/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	1120 lm	812 lm	4000K	90	38°	84x84 mm	0,40 kg
AGR02UWW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	930 lm	741 lm	2700K	90	38°	84x84 mm	0,40 kg
AGR02WW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	960 lm	762 lm	3000K	90	38°	84x84 mm	0,40 kg
AGR02NW MBK/BK	MBK/BK	COB CREE	1x10W	220-240V AC	250 mA / 25-42V DC	Included	1120 lm	812 lm	4000K	90	38°	84x84 mm	0,40 kg

AGR03

FINISHING AVAILABLE



Code	Finishing	LED type	Power	Input voltage	Output current /voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Ø	Weight
AGR03UWW MWH/BK	MWH/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	1860 lm	1482 lm	2700K	90	38°	166x84 mm	0,69 kg
AGR03WW MWH/BK	MWH/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	1920 lm	1520 lm	3000K	90	38°	166x84 mm	0,69 kg
AGR03NW MWH/BK	MWH/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	2240 lm	1624 lm	4000K	90	38°	166x84 mm	0,69 kg
AGR03UWW MBK/BK	MBK/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	1860 lm	1482 lm	2700K	90	38°	166x84 mm	0,69 kg
AGR03WW MBK/BK	MBK/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	1920 lm	1520 lm	3000K	90	38°	166x84 mm	0,69 kg
AGR03NW MBK/BK	MBK/BK	COB CREE	2x10W	220-240V AC	250 mA / 25-42V DC	Included	2240 lm	1624 lm	4000K	90	38°	166x84 mm	0,69 kg