

xsky

3 YEARS
WARRANTY



EN

Recessed spot lights for interior use, equipped with power LEDs.
Body and frame of extruded aluminum.
Frame with anodized aluminum finishing or electrostatically painted.
FRESNEL polycarbonate lens.
Constant current LED driver has to be ordered separately.

Range of applications

Decorative or general lighting.

RO

Spoturi încastrate pentru montaj în interior, echipate cu LED-uri de putere.
Corpul și rama din aluminiu extrudat.
Rama cu finisaj aluminiu anodizat sau vopsită în câmp electrostatic.
Lentilă FRESNEL din policarbonat.
Alimentatorul în curent constant se comandă separat.

Aplicații

Iluminatul decorativ sau general.

IT

Incassi fissi per interni equipaggiati con LED di potenza.
Corpo e telaio in alluminio estruso.
Telaio con finitura alluminio anodizzato o verniciato a polveri.
Lente FRESNEL in policarbonato.
Alimentatore a corrente costante da ordinare separatamente.


Campi di applicazione

Illuminazione decorativa o generale.

SK01

FINISHING AVAILABLE

MWH AL



Code	Finishing	LED type	Power	Output current / voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Ø	Weight
• SK01UWW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	106 lm	63 lm	2700K	80	45°	Ø23 mm	0,03 kg
SK01WW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	110 lm	65 lm	3000K	80	45°	Ø23 mm	0,03 kg
SK01NW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	135 lm	83 lm	4000K	80	45°	Ø23 mm	0,03 kg
• SK01UWW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	106 lm	63 lm	2700K	80	45°	Ø23 mm	0,03 kg
SK01WW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	110 lm	65 lm	3000K	80	45°	Ø23 mm	0,03 kg
SK01NW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	135 lm	83 lm	4000K	80	45°	Ø23 mm	0,03 kg

• ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

RECOMMENDED CC DRIVERS



SK02

FINISHING AVAILABLE

MWH AL



Code	Finishing	LED type	Power	Output current / voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Ø	Weight
• SK02UWW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	106 lm	63 lm	2700K	80	45°	Ø23 mm	0,03 kg
SK02WW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	110 lm	65 lm	3000K	80	45°	Ø23 mm	0,03 kg
SK02NW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	135 lm	83 lm	4000K	80	45°	Ø23 mm	0,03 kg
• SK02UWW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	106 lm	63 lm	2700K	80	45°	Ø23 mm	0,03 kg
SK02WW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	110 lm	65 lm	3000K	80	45°	Ø23 mm	0,03 kg
SK02NW45 AL	AL	POWER LED CREE	1x1W	350 mA / 2-18V DC	Excluded	135 lm	83 lm	4000K	80	45°	Ø23 mm	0,03 kg

• ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

RECOMMENDED CC DRIVERS

