

xgess ceiling

**3 YEARS
WARRANTY**

Standards: EN 60598-1:2015, EN 60598-2-1:1989,
EN 60529:1992 + A2:2013, EN 55015:2013 +
A1:2015, EN 61000-3-2:2014,
EN 61000-3-3:2013, EN 61547:2009



EN

Series of ceiling light fittings with gypsum structure, round or square shape, for LEDs reflector bulbs, PAR16. Housing of white gypsum. GU10 ceramic socket. Versions equipped with SMD or with COB LEDs.

Range of applications

Decorative interior lighting.

Lamps are not included.

RO

Serie de plafoniere cu structura din gips, formă rotundă sau pătrată, pentru becuri reflectoare cu LED-uri, PAR16. Corp din gips alb.

Dulie GU10 din ceramică. Variante echipate cu LED-uri SMD sau COB.

Aplicații

Iluminatul decorativ de interior.

Becurile nu sunt incluse.

IT

Serie di plafoniere con struttura di gesso, forma tonda o quadrata, per lampadine tipo riflettori a LED, PAR16. Corpo in gesso bianco.

Portalamпада GU10 in ceramica.

Versioni equipaggiate con LED SMD o COB.

Campi di applicazione

Illuminazione decorativa per interni.

Lampadine non incluse.

GSS31



Code	Finishing	Bulbs type	Socket	Power	Input voltage	Weight
GSS31	GP	PAR16	GU10	1x50W max.	230V AC	0,31 kg

GSS32



Code	Finishing	Bulbs type	Socket	Power	Input voltage	Weight
GSS32	GP	PAR16	GU10	1x50W max.	230V AC	0,46 kg

GSS33



Code	Finishing	Bulbs type	Socket	Power	Input voltage	Weight
GSS33	GP	PAR16	GU10	1x50W max.	230V AC	0,49 kg

GSS34




Code	Finishing	Bulbs type	Socket	Power	Input voltage	Weight
GSS34	GP	PAR16	GU10	1x50W max.	230V AC	0,65 kg

Recommended bulbs





BX-QPAR16




xgess ceiling

GSS35



Code	Finishing	LED type	Power	Input voltage	Output current / voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
GSS35WW	GP	SMD 2835 BRIDGELUX	16W	220-240V AC	350 mA / 23-46V DC	Included	1716 lm	1073 lm	3000K	80	80°	2,10 kg
GSS35NW	GP	SMD 2835 BRIDGELUX	16W	220-240V AC	350 mA / 23-46V DC	Included	1872 lm	1147 lm	4000K	80	80°	2,10 kg

GSS36



Code	Finishing	LED type	Power	Input voltage	Output current / voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
GSS36WW	GP	COB BRIDGELUX	10W	220-240V AC	200 mA / 30-42V DC	Included	898 lm	415 lm	3000K	90	80°	1,90 kg
GSS36NW	GP	COB BRIDGELUX	10W	220-240V AC	200 mA / 30-42V DC	Included	964 lm	446 lm	4000K	90	80°	1,90 kg