

xghost IP65

3 YEARS
WARRANTY



EN

Waterproof wall recessed light fittings (IP65) equipped with SMD or linear COB LEDs.

Housing of die-cast aluminum electrostatically painted.

Recessed box in polycarbonate.

Transparent polycarbonate diffuser. LED driver included.

Rubber seal at cable crossing.

Cable length 10cm.

Range of applications

Indoor and outdoor decorative lighting.

RO

Corpuri de iluminat etanșe (IP65), încastrate în perete, echipate cu un LED-uri SMD sau COB liniar.

Carcasă din aluminiu turnat, vopsită în câmp electrostatic.

Doză de încastrare din policarbonat.

Dispensur din policarbonat transparent.

Alimentator pentru LED-uri inclus.

Garnitură din cauciuc la trecerea cablului de alimentare.

Lungime cablu 10cm.

Aplicații

Iluminatul decorativ în interior sau exterior.

IT

Apparecchi da incasso a parete, protetti da polvere e umidità (IP65), equipaggiati con LED SMD o LED COB lineare.

Corpo in alluminio pressofuso, verniciato a polveri.

Scatola da incasso in policarbonato.

Diffusore in policarbonato trasparente.

Alimentatore LED incluso.

Guarnizione in gomma per passaggio cavo di alimentazione.

Lunghezza cavo 10cm.

Campi di applicazione



Illuminazione decorativa per interni ed esterni.



GS02

FINISHING AVAILABLE

MWH BK





Code	Finishing	LED type	Power	Input voltage	Driver	LED flux	System flux	CCT	CRI	Optics	Light distribution	Weight
GS02WWIP65 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	180 lm	89 lm	3000K	80	Asymetrical	74x74 mm	0,20 kg
GS02NWIP65 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	192 lm	98 lm	4000K	80	Asymetrical	74x74 mm	0,20 kg
GS02WWIP65 BK	BK	SMD 5730 EPISTAR	2W	100-240V AC	Included	180 lm	89 lm	3000K	80	Asymetrical	74x74 mm	0,20 kg
GS02NWIP65 BK	BK	SMD 5730 EPISTAR	2W	100-240V AC	Included	192 lm	98 lm	4000K	80	Asymetrical	74x74 mm	0,20 kg

GS03

FINISHING AVAILABLE

MWH BK



Compatibile con scatola da incasso (S503EF)



Code	Finishing	LED type	Power	Input voltage	Driver	LED flux	System flux	CCT	CRI	Optics	Light distribution	Weight
● GS03WWIP65 MWH	MWH	LINEAR COB	3W	230V AC	Included	190 lm	108 lm	3000K	80	Asymetrical	110x70 mm	0,15 kg
● GS03NWIP65 MWH	MWH	LINEAR COB	3W	230V AC	Included	210 lm	117 lm	4000K	80	Asymetrical	110x70 mm	0,15 kg
● GS03WWIP65 BK	BK	LINEAR COB	3W	230V AC	Included	190 lm	108 lm	3000K	80	Asymetrical	110x70 mm	0,15 kg
● GS03NWIP65 BK	BK	LINEAR COB	3W	230V AC	Included	210 lm	117 lm	4000K	80	Asymetrical	110x70 mm	0,15 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE