


MT 128 LED



RECESSED DOWNLIGHTS
SPOTURI ÎNCASTRATE
INCASSI




White (WH)



Aluminum (AL)

PHOTOMETRIC DATA



Code	LED type	Power	Input voltage	LED flux	System flux	CCT	Driver	Optics	CRI		Weight
70563 WH	COB LED EPISTAR	1x5W	220-240V AC	510 lm	349 lm	3000K	Included	30°	80	\varnothing 75 mm	0,22 kg
70363 WH	COB LED EPISTAR	1x5W	220-240V AC	550 lm	368 lm	4000K	Included	30°	80	\varnothing 75 mm	0,22 kg
70564 AL	COB LED EPISTAR	1x5W	220-240V AC	510 lm	349 lm	3000K	Included	30°	80	\varnothing 75 mm	0,22 kg
70364 AL	COB LED EPISTAR	1x5W	220-240V AC	550 lm	368 lm	4000K	Included	30°	80	\varnothing 75 mm	0,22 kg

EN

Round adjustable recessed downlights, for interior mounting, equipped with COB LEDs.

RO

Corpuri de iluminat rotunde, orientabile, încastrate, pentru montaj în interior, echipate cu LED-uri COB.

IT

Faretti rotondi orientabili da incasso per interni, dotati di LED COB.