


RECESSED DOWNLIGHTS
SPOTURI ÎNCASTRATE
INCASSI



White (WH)



White (WH)



Nickel mat (NM)



Polish brass (PB)



Antique brass (AB)



Red antique brass (RAB)



Pearl chrome/Chrome (PC/CH)



Pearl gold/Silver (PG/S)



Pearl silver/Gold (PS/G)




Gun metal/Chrome (GM/CH)



Chrome (CH)

PHOTOMETRIC DATA



Code	Bulbs type	Socket	Power	Input voltage	Electric gear		Weight
70001 WH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70002 CH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70081 NM	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70003 PB	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70237 AB	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70094 RAB	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70006 PS/G	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70005 PG/S	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70007 PC/CH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg
70004 GM/CH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,13 kg

EN

Recessed round light fittings, adjustable, for low voltage (12V) halogen lamps, QR-CB51 type, for LED modules or LED bulbs with same dimensions and type of socket.

RO

Corpuri de iluminat rotunde încastrate, orientabile, pentru lămpi halogen la joasă tensiune (12V) tip QR-CB51, pentru module cu LED-uri sau pentru becuri cu LED-uri care au aceleași dimensiuni și tip de soclu.

IT

Faretti da incasso rotondi orientabili, per lampade alogene a bassa tensione (12V) QR-CB51, per moduli a LED o per lampadine a LED con le stesse dimensioni e tipo di attacco.