


ELC 3072



Smarter®

RECESSED DOWNLIGHTS
SPOTURI ÎNCASTRATE
INCASSI



White (WH)



White (WH)



Mat chrome (MC)



Chrome (CH)



Polish brass (PB)





Mat brass (MB)



Gun metal (GM)

PHOTOMETRIC DATA



Code	Bulbs type	Socket	Power	Input voltage	Electric gear		Weight
70153 WH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg
70154 CH	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg
70156 MC	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg
70155 PB	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg
70157 MB	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg
70158 GM	QR-CB51 / LED	GU5.3	1x50W max.	12V AC	Not included	Ø75 mm	0,14 kg

EN

Recessed round light fittings, adjustable, for low voltage (12V) halogen lamps, QR-CB51 type, for LED modules or LED bulbs with same dimensions and type of socket.

RO

Corpuri de iluminat rotunde încastrate, orientabile, pentru lămpi halogen la joasă tensiune (12V) tip QR-CB51, pentru module cu LED-uri sau pentru becuri cu LED-uri care au aceleași dimensiuni și tip de soclu.

IT

Faretti da incasso rotondi orientabili, per lampadine alogene a bassa tensione (12V) QR-CB51, per moduli a LED o per lampadine a LED con le stesse dimensioni e tipo di attacco.