

XBULB

LED LIGHT SOURCES
SURSE DE LUMINĂ CU LED
SORGENTI LUMINOSE A LED



EN

Bulbs equipped with SMD LEDs, GU10, E27 or G53 sockets.

HOUSING

Housing and frame of aluminium, electrostatically painted in white color.

OPTICAL SYSTEM

Satin polycarbonate diffuser lens.

ELECTRIC GEAR

LEDs driver included.

RANGE OF APPLICATIONS

Equipping of downlights or projectors with GU10/E27/G53 sockets.

RO

Becuri echipate cu LED-uri SMD, cu dulii GU10, E27 sau G53.

CORP

Carcasă și ramă din aluminiu, vopsite în câmp electrostatic culoare albă.

SISTEM OPTIC

Lentilă dispersor din policarbonat satinat.

APARATAJ DE ALIMENTARE

Alimentator LED-uri inclus.

APLICAȚII

Echiparea corpurilor încastrate sau a proiectoarelor echipate cu dulii GU10/E27/G53.

IT

Lampadine equipaggiate con LED SMD, con attacchi GU10, E27 o G53.

CORPO

Corpo e cornice in alluminio verniciato a polveri, colore bianco.

SISTEMA OTTICO

Lente diffusore in policarbonato satinato.

ALIMENTAZIONE

Alimentatore LED incluso.

CAMPI DI APPLICAZIONE

Equipaggiamento di incassi o proiettori dotati di attacchi GU10/E27/G53.



BX-QPAR16



| Code | Finishing | Power | Socket | Type of LED | Input voltage | LED flux | System flux | CCT | CRI | Optics | Weight |
|--------------------|-----------|-------|--------|-------------|---------------|----------|-------------|-------|-----|--------|---------|
| BX-QPAR16WW | ○ | 7W | GU10 | SMD 2835 | 220-240V AC | 620 lm | 457 lm | 3000K | 80 | 36° | 0,06 kg |
| BX-QPAR16NW | ○ | 7W | GU10 | SMD 2835 | 220-240V AC | 650 lm | 484 lm | 4200K | 80 | 36° | 0,06 kg |

BX-PAR20



BX-PAR30



| Code | Finishing | Power | Socket | Type of LED | Input voltage | LED flux | System flux | CCT | CRI | Optics | Weight |
|-------------------|-----------|-------|--------|-------------|---------------|----------|-------------|-------|-----|--------|---------|
| BX-PAR20WW | ○ | 8W | E27 | SMD 2835 | 220-240V AC | 840 lm | 619 lm | 3000K | 80 | 38° | 0,09 kg |
| BX-PAR20NW | ○ | 8W | E27 | SMD 2835 | 220-240V AC | 880 lm | 658 lm | 4200K | 80 | 38° | 0,09 kg |
| BX-PAR30WW | ○ | 12W | E27 | SMD 2835 | 220-240V AC | 890 lm | 931 lm | 3000K | 80 | 38° | 0,31 kg |
| BX-PAR30NW | ○ | 12W | E27 | SMD 2835 | 220-240V AC | 1260 lm | 989 lm | 4200K | 80 | 38° | 0,31 kg |

BX-QR111



| Code | Finishing | Power | Socket | Type of LED | Input voltage | LED flux | System flux | CCT | CRI | Optics | Weight |
|-------------------|-----------|-------|--------|-------------|---------------|----------|-------------|-------|-----|--------|---------|
| BX-QR111WW | ○ | 12W | G53 | SMD 2835 | 220-240V AC | 1320 lm | 946 lm | 3000K | 80 | 38° | 0,21 kg |
| BX-QR111NW | ○ | 12W | G53 | SMD 2835 | 220-240V AC | 1340 lm | 1003 lm | 4200K | 80 | 38° | 0,21 kg |

PHOTOMETRIC DATA

