



Wiring devices system characterized by its profile and shape inspired to the Chorus family feeling. Wide range of plates with an Italian design, articulated into two families, GEO and LUX cover plates, available in many materials and finishes. The range is available in three colors: glossy white, satin black, painted titanium and fits in 3x3 inches (1-gang) and 3x6 inches (2-gang) British Standard boxes. Range expandable thanks to the Chorus modular devices.

Categorie	3 gang one-way switch	Tip	3 modul
Tastă	Neutru	Culoare	Alb
Descriere	1P - 10AX	Tensiune	250 V ac
Rated power of 230V LED lamps	100 W	Standard	EN 60669-1
Rezistență la tensiunea de test	2000 V la 50 Hz pentru 1 minut	Rezistența izolației	> 5 MOhm
Terminale de cablare	Cu șuruburi	Funcționare prelungită (nr. de schimbări de poziție)	40.000 la In 250 V ac cosφ=0,6
Termo-presiune cu bilă	125 °C	Glow Test conductori	850 °C
Strângere terminal la tracțiune cablu	> 50 N	Capacitate strângere terminal cabluri flexibile (mm2)	min. 1,5 - max. 2,5
Capacitate strângere terminal cabluri rigide (mm2)	min. 1,5 - max. 2,5		

DIMENSIONAL

TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

