




Complete system for the connection and distribution of LAN networks in residential and tertiary sector environments.

The range includes fibre optic solutions, wall panels, floor cabinets and copper wiring products.

The Data Center series provides all the products necessary to create a multi-service fibre optic infrastructure for residential buildings, in full compliance with all the indications dictated by the new IEC Guide 306-2 and Law 164/14.

Categorie	Optical connector	Cable colour	Alb
No. optical fibers	1	Lungimea	2 m
Ø sheath	0,9 mm	For connectors	SC/APC - SC/APC
Clasificare	G.657.A2 / B6_a2 Bend Insensitive	Ø core	9 µm
Ø cladding	125 µm	Outer jacket	LSZH
Cablu	Tight - OS2	Minimum bend radius (Dynamic)	25x cable diameter
Minimum bend radius (Static)	15x cable diameter	Max attenuation (@1310 nm / @1550 nm)	0.35 / 0.2 dB/Km
Temperatură de funcționare	From -20°C to +60°C		

### DIMENSIONAL



### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 19/08/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice