




The IP40 protected decorative enclosures are available in sizes from 8 to 72M. They provide superior aesthetic integration and are equipped with screw wiring multipolar terminal blocks, 80 A IP 20. They are available with smoked transparent doors or with blank doors that can be equipped with safety lock, characterized by the "PUSH" opening and closing. The terminal blocks allow to create simple and neat wiring reducing the set-up time of the enclosure.

Clasă izolație	II (conform standardelor IEC 61140)	Culoare	Alb RAL 9016
Dim. exterioare LxHxP (mm)	280x225x100	Clasă de protecție IP	IP40
Putere disipabilă (W)	22	Cod IK	IK08
Tensiune nominală	400 V	Culoare ușă	Transparent fumuriu
Cutii cu borne	80 A - orificii cu șuruburi IP20	Nr. module EN 50022	12
Curent nominal	125 A	Glow Test conductori	650 °C
Temperatură de operare	-25 +60 °C	Tip de material	Fără halogen conform EN 60754-2
Electrocod	0321	Termo-presiune cu bilă	70 °C
Accesorii pentru restabilirea izolației	Capete de șuruburi (GW44623) sau console de fixare în rășină (GW44621)	Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49
Tensiune izolație	750 V	Stâlp 1 (mm ²)	N/E (3x16) + (11x10)
Stâlp 2 (mm ²)	N/E (3x16) + (11x10)		



DIMENSIONAL

TECHNICAL SYMBOLOGY




IP
IP40

IK
IK08

GWT
650 °C



HF
HALOGEN FREE
Fără halogen conform EN 60754-2



STANDARDS/APPROVALS

