



German standard wall mounting enclosure equipped with bipolar terminal blocks and two interchangeable flanges (1 flange with knock-out elements and 1 flange with quick entry cable glands).

| | | | |
|----------------------------------|---------------------|----------------------------------|---|
| Clasă izolație | II | Culoare | Gri RAL 7035 |
| Dim. exterioare LxHxP (mm) | 298x420x140 | Clasă de protecție IP | IP65 |
| Instalare | Perete | Cod IK | IK07 |
| Culoare ușă | Transparent fumuriu | Cutie borne N (mm ²) | (3x25)+(10x10) |
| Cutie borne T (mm ²) | (3x25)+(10x10) | Nr. module EN 50022 | 24 (12X2) |
| Glow Test conductori | 750 °C | Standard | IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1 |
| Temperatură de operare | -25 +60 °C | Electrocod | 0321 |
| Termo-presiune cu bilă | 70 °C | Stâlp 1 (mm ²) | N (3x35) + (10x10) |
| Stâlp 2 (mm ²) | E (3x35) + (10x10) | | |



DIMENSIONAL

TECHNICAL SYMBOLOGY



II

IP

IP65

IK

IK07

GWT

750 °C



-25 +60 °C



70 °C

STANDARDS/APPROVALS

