



Watertight enclosure for emergency systems, equipped with illuminated push-button and 2 contacts 1NO+1NC that can be expanded up to 4 contacts. The enclosure has the pre-arrangement for use of green led to indicate the good condition of emergency circuit. It is pre-arranged with a short or long push-button for deliberate operation, or with an intrinsic safety function. Thanks to the emergency hammer, available as an accessory, sealable mask and halogen free materials are ideally suited for applications in areas open to public.

Curent nominal (A)	125	Clasă izolație	II
Culoare	RAL 3000 Roșu	Dim. exterioare LxHxP (mm)	120x120x50
Clasă de protecție IP	IP55	Instalare	Perete
Material	Tehnopolimer	Cod IK	IK08
Tensiune nominală (V)	400	Dotări	Buton cu revenire + 2 contacte
Glow Test conductori	650 °C	Temperatură de operare	-25 +60 °C
Tip de material	Fără halogen conform EN 60754-2	Electrocod	0321
Nr. de contacte care pot fi instalate	4	Termo-presiune cu bilă	70 °C
Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Tensiune izolație	750 V



## DIMENSIONAL

### TECHNICAL SYMBOLOGY



II

**IP**

IP55

**IK**

IK08

**GWT**

650 °C



-25 +60 °C

**HF**

Fără halogen  
conform EN 60754-2



70 °C

### STANDARDS/APPROVALS

