



Watertight flush-mounting enclosures for emergencies and special applications with rail DIN. Available in red RAL 3000 or grey RAL7035 colours. Thanks to the emergency hammer, available as an accessory, sealable mask and halogen free materials are ideally suited for applications in areas open to public.

Curent nominal (A)	125	Clasă izolație	II
Culoare	RAL 3000 Roșu	Dim. exterioare LxHxP (mm)	145x200x70
Clasă de protecție IP	IP55	Instalare	Doze sub tencuială
Material	Tehnopolimer	Cod IK	IK08
Tensiune nominală (V)	400	Glow Test conductori	650 °C
Temperatură de operare	-15 +60 °C	Tip de material	Fără halogen conform EN 60754-2
Electrocod	0321	Termo-presiune cu bilă	70 °C
Standard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Tensiune izolație	750 V
Putere disipabilă (W)	12	Nr. module EN 50022	4



## DIMENSIONAL

### TECHNICAL SYMBOLOGY



II

**IP**

IP55

**IK**

IK08

**GWT**

650 °C



-15 +60 °C

**HF**

Fără halogen  
conform EN 60754-2



70 °C

### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 19/08/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice