



70 RT HP is a new range of 16A to 160A switch disconnectors in isolating material and metal, supplied in a box. Available in control and emergency versions, the range is completed by board versions for front-panel or DIN rail assembly, in 16 to 63A options, all of which can be equipped with auxiliary contacts. These devices have been designed to deliver the ultimate in reliability, functionality and performance. They offer a technologically advanced solution that simplifies installation, reduces wiring times and ensures maximum safety and robustness, even in the most demanding conditions, thanks to the use of high-performance materials.

Versiune	Doză	Material	Clasă
Tip	Pentru urgență	Curent nominal (A)	40
Nr. stâlpi	2P	Întrerupător	Rotary isolator
Clasă de protecție IP	IP66/IP67/IP69	Cod IK	IK08
Temperatură ambiantă	-25 +60 °C	Lid screws (no. and type)	4 sigilabile la 1/4 de tur
Intrare orificii	2 x M20/25 + 2 x M20/25	Blocabil	YES (max. 3 locks in OFF)
Tip de accesorii	Max. 2 auxiliary contacts	Current in AC22 (415V)	40
Current in AC23 (415V)	40	Secțiune cabluri	Max 10 mm ²
Dim. exterioare LxHxP (mm)	125x150x75,5	Electrocod	1742



DIMENSIONAL



TECHNICAL SYMBOLOGY

IP **IK**

IP66/IP67/IP69

IK08

STANDARDS/APPROVALS

