




The range consists of seven different sizes of connection and junction boxes made of die-cast aluminium alloy. Suitable for every application, they are particularly recommended in industrial environments and on machinery (for particular applications is necessary contact GEWISS Service Technical Assistance). The boxes can be surface-mounted from both the inside and outside. The earth terminal (for protection against indirect contact) is on both the bottom and the lid. The outside of the box is covered with epoxy-polyester paint to ensure the maximum resistance with perfect design integration. There are also unpainted versions and ATEX versions for Zone 2 (G) and Zone 22 (D). The stainless steel fixing screws of the cover are unlosable, the bottom of the box has an insert for the earth connection and is prepared for the assembly of the DIN rail. Accessories include back-mounting plates in galvanised steel (available from the second dimension).

Material	Painted aluminium alloy	Culoare	Gri metalizat
Clasă de protecție IP	IP66	Dim. interioare LxHxD (mm)	178x156x75
Cod IK	IK08	Dim. exterioare LxHxP (mm)	189x167x80
Ø max orificii executabile	37 mm	Șuruburi capac (nr. și tip)	4 - Stainless steel with double slotted head
Capac	Plat	Temperatură de operare	-60 +100 °C
Pereți	Neted	Electrocod	0230



DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP66

IK

IK08

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 19/08/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice