



# Belanko™

# **Double pole Switches 20 A**

#### Cat. No(s): 6 170 70/71/72/73 - 6 172 70 - 6 173 70/71/72/73 - 6 174 70/71/72/73








#### 1. USE


Double pole switches, large rocker, complete delivered. For surface or flush-mounting back box to be min. 35 mm deep. Supplied with 2 screws M3.5 for BS boxes..

## 2. RANGE

	White	Ivory	Dark Grey	Brown
1 gang 1-way switch + red neon indicator	6 170 70	6 172 70	6 173 70	6 174 70
1 gang 1-way switch + red neon indicator + earth connection	6 170 71	-	6 173 71	6 174 71
1 gang 1-way switch + red neon indicator + earth connection with "Water Heater" marking	6 170 72	-	6 173 72	6 174 72
1 gang 1-way switch without neon	6 170 73	-	6 173 73	6 174 73

# 3. OVERALL DIMENSIONS (mm)





Α	В	С	D
86	86	38.5	14.5

## 4. CONNECTION

Type of terminals: with screws

Terminal capacity: 2 x 4 mm<sup>2</sup> - 3 x 2.5 mm<sup>2</sup> - 1 x 6 mm<sup>2</sup>

Stripping length: 8 mm Screwdriver: 4 mm flat blade

Compatible with flexible or rigid cables

## **5. TECHNICAL CHARACTERISTICS**

#### ■ 5.1 Mechanical characteristics

Impact tests: IK 04

Penetration by solid bodies/liquids: IP 40

# ■ 5.2 Material characteristics

Thermoplastic with glossy finish (White, Ivory)

Colour: White T084: PC Ivory: PC

Dark Grey: PC painted

Brown: painted

Halogen free

**UV** resistant

Self-extinguishing:

850° C / 30 s for insulating parts holding live parts in place. 650° C / 30 s for other parts made of insulating materials.

#### ■ 5.3 Electrical characteristics

Voltage: 250 V~ Current: 20 A Frequency: 50/60 Hz

# ■ 5.4 Climatic characteristics

Storage temperature: -  $10^{\circ}$  C to +  $70^{\circ}$  C Use temperature:  $-5^{\circ}$  C to  $+35^{\circ}$  C

## 6. CLEANING

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistance to the following cleaning substances:

Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Diluted pure bleach 10%, Glass cleaning product.

Caution: An initial test is required for the use of other special maintenance products.

### 7. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing. See e.catalogue.

Technical data sheet: F01056EN/02 Updated: 18/01/2017 Created: 18/01/2010