

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40



CONTENTS	PAGES
1. Description - Use .....	1
2. Range .....	1
3. Overall dimensions .....	1
4. Preparation - Connection .....	1
5. General characteristics .....	2
6. Conformities and approvals .....	15
7. Characteristic curves .....	16
8. Auxiliaries and accessories .....	21

## 1. DESCRIPTION - USE

Thermo-magnetic circuit breaker (MCB) with positive contact indication for control, protection and isolation of electrical circuits.

### Symbol:



### Technology:

- . Current limiting device.
- . 1,5 module (26,7 mm) per pole.
- . Trip free mechanism.

## 2. RANGE

### Number of Poles:

- . 2P / 3P / 4P.

### Rated current In:

- . 10 / 16 / 20 / 25 / 32 / 40 / 50 / 63 C curve.

### Tripping characteristics and magnetic tripping calibrations:

- . C curve (between 5 and 10 In).

### Thermal threshold:

- . Non operating current (I<sub>nf</sub>): 1,05 In.
- . Operating current (I<sub>f</sub>): 1,3 In.

### Rated Voltage / Frequency:

- . 230 / 400 V ~, 50 / 60 Hz with standard tolerances.
- . 240 / 415 V ~, 50 / 60 Hz with standard tolerances.
- . 125 V per pole in direct current.


### Maximum operating voltage:

- . 500 V ~, 50 / 60 Hz with derating of breaking capacity.

### Breaking capacity:

- . 36 kA according to IEC/EN/NF 60947-2

## 3. OVERALL DIMENSIONS



N° of poles	"X" (mm)
2P	<b>53,4 mm</b>
3P	<b>80,1 mm</b>
4P	<b>106,8 mm</b>


## 4. PREPARATION - CONNECTION

### Fixing:

- . On symmetric rail EN/IEC 60715 or DIN 35.

### Operating position:

- . Vertical    Horizontal    Upside down    On the side



### Supply:

- . Either from the top or the bottom.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 4. PREPARATION – CONNECTION *(continued)*

### Terminal depth:

- . 19 mm.
- . It is possible to separate the terminals by retractable insulation shields.

### Stripping length recommended:

- . 17 mm for main terminals.

### Screw head:

- . Mixed, slotted and Pozidriv n°2.

### Tightening torque:

- . Recommended: 3 Nm.
- . Mini 2.5 Nm. Maxi 3.5 Nm.

### Tools required:

- . For the terminals: Pozidriv n°2 or flat screwdriver 5,5 mm (6 mm maximum).
- . For fixing: flat screwdriver 5,5 mm (6 mm maximum).

### Connectable section:

	Copper cable	
	Without ferrule	Without ferrule
Rigid cable	1 x 1,5mm <sup>2</sup> to 50mm <sup>2</sup> 2 x 1,5mm <sup>2</sup> to 16mm <sup>2</sup>	-
Flexible cable	1 x 1,5mm <sup>2</sup> to 35mm <sup>2</sup> 2 x 1,5mm <sup>2</sup> to 10mm <sup>2</sup>	1 x 1,5mm <sup>2</sup> to 35mm <sup>2</sup>

### Manual actuation of the circuit-breaker:

- . Ergonomic 2 position handle:
  - 0 / OFF: Device open.
  - I / ON: Device closed.

### Contact status display:

- . By marking of the associated m.c.b. handle:
  - “O-Off” white on a green background = contacts opened.
  - “I-On” white on a red background = contacts closed.
- . By mechanical indicator on front face:
  - Green = contacts opened.
  - Red = contacts closed.

### Sealing:

- . Possible in “Open” position (OFF) or “Close” position (ON).

### Lockout::


- . By 5 mm padlock (cat. n° 4 063 13) or 6 mm padlock (cat. n° 0 227 97) with padlock support (cat. N4 063 03) in “Open” position


### Consignment:

- . On site padlocking system, possible only open circuit - 0 / OFF handle position - with 1,5mm<sup>2</sup> stripped wire for example or 2,4mm wide Colring.

## 5. GENERAL CHARACTERISTICS

### Front side marking:

- . By permanent ink pad printing showing:
  - Trade name: DX<sup>3</sup>
  - Breaking curve
  - Rated current (in A)
  - Icu in kA, Breaking capacity according to IEC/ EN 60947-2 standard (36kA)
  - Catalogue number and logo 
  - Mark: Legrand



### Short-circuit breaking capacity:

- . Alternate current 50/60Hz, single-phase or three-phase network (50/60 Hz AC), according to IEC 60947-2. C curve

Un		2P	3P / 4P
110 V~	Icu	100 kA	-
230 V~		72 kA	72 kA
400 V~		36 kA	36 kA
440 V~		25 kA	25 kA
500 V~		12,5 kA	12,5 kA

Un	Ics	75% of Icu	75% of Icu
110 V~	Ics	75% of Icu	75% of Icu
230 V~			
400 V~			

### Short-circuit breaking capacity of only one pole:

- . In three-phase network 220 / 380 V~ to 240 / 415 V~
  - for TN neutral system, Icn1 = 36 kA (under 220 to 240 V~)
  - for IT neutral system, Iit = 9 kA (under 380 to 415 V~)
- . In three-phase network 110 / 220 V~ to 120 / 240 V~
  - for TN neutral system, Icn1 = 72 kA (under 110 to 127 V~)
  - for IT neutral system, Iit = 18 kA (under 220 to 240 V~)


# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS (continued)

### Short-circuit breaking capacity in DC current:

. Direct current according IEC 60947-2



Un		2P	3P	4P
24 ÷ 48 V d.c.	<b>I<sub>cu</sub></b>	<b>36 kA</b>	-	-
110 V d.c.		<b>36 kA</b>	<b>36 kA</b>	-
230 V d.c.		-	-	<b>36 kA</b>

24 ÷ 48 V d.c.	<b>I<sub>cs</sub></b>	<b>36 kA</b>	-	-
110 V d.c.		<b>36 kA</b>	<b>36 kA</b>	-
230 V d.c.		-	-	<b>36 kA</b>

### Minimum operating voltage :

. 12 V a.c. / d.c. per pole.

### Pulse rated voltage:

. U<sub>imp</sub> = 6 kV (wave 1.5 / 50 μs).

### Insulation rated voltage:

. U<sub>i</sub> = 500 V.

### Pollution degree::

. 3.

### Dielectric strength:

. 2500 V.

### Operation at 400Hz:

. The magnetic thresholds increase by 45%.

### Load to close and open of a pole through the handle:

. 0,17 Nm per pole to close.

. 0,09 Nm per pole to open.

### Mechanical endurance according to IEC 60947-2 :

. 20 000 operations without load

. 10 000 operations with load (under I<sub>n</sub> x Cos φ=0.9)

. 2 000 operations with load (under I<sub>n</sub> in DC current)

### Enclosure material:

. Polyester.

. Characteristics of this material: self extinguishing, heat and fire resistant according to EN 60898-1, glow-wire test at 960°C for external parts made of insulating material necessary to retain in position current-carrying parts and parts of protective circuit (650°C for all other external parts made of insulating material).

### Average weight per pole:

. 0,220 kg.

### Volume when packed:

	Volume (dm <sup>3</sup> )
Double pole	<b>0,63</b>
Triple / Four pole	<b>1,14</b>

### Ambient operating temperature:

. Min. = -25°C. Max. = +70°C

### Ambient storage temperature:

. Min. = -40°C. Max. = +70°C

### Protection class:

. Protection index of terminals against solid and liquid bodies:

IP 20 (according to IEC 529, EN 60529 et NF C 20-010).

. Protection index of the box against solid and liquid bodies:

IP 40 (according to IEC 529, EN 60529 et NF C 20-010).

. Protection index against mechanical shocks:

IK 02 (according to EN 50102 et NF C 20-015).

### Resistance to sinusoidal vibrations:

. According to IEC 60068-2-35.

. Axis : x, y, z.

. Frequency range: 5÷100 Hz ; duration 90 minutes

. Displacement (5÷13,2 Hz) : 1mm.

. Acceleration (13,2÷100 Hz) : 0,7g (g=9,81 m/s<sup>2</sup>)

### Recognition:

. Recognition of the circuit by insertion of a label in the label holder.

### Power dissipated per pole at I<sub>n</sub> (in W) :

. mcb C curve

I <sub>n</sub>	10 A	16 A	20 A	25 A	32 A
1P à 4P	<b>1,9</b>	<b>2,75</b>	<b>4,72</b>	<b>2,8</b>	<b>4,4</b>

I <sub>n</sub>	40 A	50 A	63 A
1P à 4P	<b>4,6</b>	<b>4,32</b>	<b>6,05</b>

. Impedance per pole (Ω) =  $\frac{\text{Power dissipated}}{I_n^2}$

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*

### Derating of circuit-breakers according to ambient temperature :

. The nominal characteristics of a circuit breaker are modified according to the ambient temperature inside the cabinet or the enclosure where the circuit breaker is located.

. Reference temperature: 40°C according IEC/EN 60947-2.

In (A)	Ambient Temperature / In									
	- 25°C	- 10°C	0°C	10°C	20°C	30°C	40°C	50°C	60°C	70°C
10	14.0	12.5	11.5	11.1	10.7	10.3	10.0	9.7	9.3	9.0
16	21.9	20.0	18.7	18.0	17.3	16.6	16.0	15.4	14.7	14.1
20	27.7	25.0	23.2	22.4	21.6	20.8	20.0	19.2	18.4	17.6
25	34.5	31.5	29.5	28.3	27.2	26.0	25.0	24.0	22.7	21.7
30	41.7	38.3	36.0	34.5	33.0	31.5	30.0	28.8	27.3	26.1
32	45.8	41.0	37.8	36.5	34.9	33.3	32.0	30.7	29.1	27.8
40	55.5	51.0	48.0	46.0	44.0	42.0	40.0	38.0	36.0	34.0
50	70.0	64.0	60.0	57.5	55.0	52.5	50.0	47.5	45.0	42.5
63	88.1	80.6	75.6	72.5	69.9	66.1	63.0	59.8	56.1	52.9

### Derating of MCB for use with fluorescent lights:

Ferromagnetic and electronic ballasts have a high inrush current for a short time. These currents can cause the tripping of circuit breakers. At the time of the installation, it should take into account the maximum number of ballasts per circuit breaker that the manufacturers of lamps and ballasts indicate in their catalogues.

### Influence of the altitude:

	≤2000 m	3000 m	4000 m	5000 m
Dielectric holding	3000 V	2500 V	2000 V	1500 V
Max operational Voltage	400 V	400 V	400 V	400 V
Derating at 40°C	none	none	none	none

### Derating of RCCBs function of the number of devices side by side:

When several RCCBs are juxtaposed and operate simultaneously, the thermal evacuation of the poles is limited. This results in an increase in operating temperature of the circuit breakers which can cause unwanted tripping. It is recommended to apply the following coefficients to the rated currents.

Number of circuit breakers side by side	Coefficient
2 - 3	0.9
4 - 5	0.8
6 - 9	0.7
≥ 10	0.6

These values are given by the recommendation of IEC 60439-1, NF C 63421 and EN 60439-1 standards.

To avoid to have to use these coefficients, it is necessary to allow a good ventilation and to separate the devices with 0.5 module spacing elements (cat. N° 4 063 07).

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*:

### Back-up protection between modular circuit-breakers and fuses, three-phase network (+ neutral) 400 / 415 V~ according to IEC/EN 60947-2:

For TT or TN neutral system in 230/400 V network, to know the breaking capacity of the combination of a double pole breaker (connected between phase and neutral under 230V) downstream of a triple-pole circuit-breaker, take the values shown in Tables 230/400V.

		Fuse upstream									
		gG type									
m.c.b. downstream		≤20A	25A	32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C curve	10A	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	16A	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	20A	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	25A	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	32A	-	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA
	40A	-	-	-	-	-	100kA	100kA	100kA	100kA	100kA
	50A	-	-	-	-	-	-	100kA	100kA	100kA	100kA
	63A	-	-	-	-	-	-	-	100kA	100kA	100kA

		Fuse upstream									
		aM type									
m.c.b. downstream		≤20A	25A	32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C curve	10A	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	16A	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	20A	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	25A	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	32A	-	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA
	40A	-	-	-	-	-	100kA	100kA	100kA	100kA	100kA
	50A	-	-	-	-	-	-	100kA	100kA	100kA	100kA
	63A	-	-	-	-	-	-	-	100kA	100kA	100kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*:

### Back-up protection between modular circuit-breakers, three-phase network (+ neutral) 400 / 415 V~ according to IEC/EN 60947-2:

For TT or TN neutral system in 230/400 V network, to know the breaking capacity of the combination of a double pole breaker (connected between phase and neutral under 230V) downstream of a triple-pole circuit-breaker, take the values shown in Tables 230/400V.

		m.c.b. upstream				
		DX <sup>3</sup> 50kA				
		B, C and D Curves				
m.c.b. downstream		≤25A	32A	40A	50A	63A
DX <sup>3</sup> 36kA C Curve	≤6A	50kA	50kA	50kA	50kA	50kA
	10A	50kA	50kA	50kA	50kA	50kA
	16A	50kA	50kA	50kA	50kA	50kA
	20A	50kA	50kA	50kA	50kA	50kA
	25A	-	50kA	50kA	50kA	50kA
	32A	-	-	50kA	50kA	50kA
	40A	-	-	-	50kA	50kA
	50A	-	-	-	-	50kA
	63A	-	-	-	-	-

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

### Back-up protection between modular circuit-breakers and M.C.C.B.s, three-phase network (+ neutral) 400 / 415 V~ according to IEC/EN 60947-2:

For TT or TN neutral system in 230/400 V network, to know the breaking capacity of the combination of a double pole breaker (connected between phase and neutral under 230V) downstream of a triple-pole circuit-breaker, take the values shown in Tables 230/400V.

		m.c.c.b. upstream										
		DPX <sup>3</sup> 160 / DPX <sup>3</sup> 160 + diff.							DPX 250ER			
		50kA							50kA			
m.c.b. downstream		16A	25A	40A	63A	80A	100A	125A	160A	100A	160A	250A
DX <sup>3</sup> 36kA C curve	≤6A	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	10A	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	16A		50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	20A		50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	25A			50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	32A			50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	40A				50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	50A				50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	63A					50kA	50kA	50kA	50kA	50kA	50kA	50kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## Back-up protection between modular circuit-breakers and M.C.C.B.s, three-phase network (+ neutral) 400 / 415 V~ according to IEC/EN 60947-2:

For TT or TN neutral system in 230/400 V network, to know the breaking capacity of the combination of a double pole breaker (connected between phase and neutral under 230V) downstream of a triple-pole circuit-breaker, take the values shown in Tables 230/400V.

		m.c.c.b. upstream									
		DPX <sup>3</sup> 250 / DPX <sup>3</sup> 250+diff.				DPX H / L 250					
		70kA				70 – 100kA					
		m.c.b. downstream		100A	160A	200A	250A	25A	40A	63A	100A
DX <sup>3</sup> 36kA C curve	10A	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	16A	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	20A	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA	50kA
	25A	50kA	50kA	50kA	50kA	-	50kA	50kA	50kA	50kA	50kA
	32A	50kA	50kA	50kA	50kA	-	50kA	50kA	50kA	50kA	50kA
	40A	50kA	50kA	50kA	50kA	-	-	50kA	50kA	50kA	50kA
	50A	50kA	50kA	50kA	50kA	-	-	50kA	50kA	50kA	50kA
	63A	50kA	50kA	50kA	50kA	-	-	-	50kA	50kA	50kA

		m.c.c.b. upstream					
		DPX H / DPX L 630MT					
		70 – 100kA					
		m.c.b. downstream		250A	320A	400A	500A
DX <sup>3</sup> 36kA C curve	10A	50kA	50kA	50kA	50kA	50kA	50kA
	16A	50kA	50kA	50kA	50kA	50kA	50kA
	20A	50kA	50kA	50kA	50kA	50kA	50kA
	25A	50kA	50kA	50kA	50kA	50kA	50kA
	32A	50kA	50kA	50kA	50kA	50kA	50kA
	40A	50kA	50kA	50kA	50kA	50kA	50kA
	50A	50kA	50kA	50kA	50kA	50kA	50kA
	63A	50kA	50kA	50kA	50kA	50kA	50kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*:

Back-up protection between modular circuit-breakers and fuses, three-phase network (+ neutral) 230 / 240 V~ according to IEC/EN 60947-2:

		Fuse upstream									
		gG type									
m.c.b. downstream		≤20A	25A	32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C curve	10A	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	16A	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	20A	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	25A	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	32A	-	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA
	40A	-	-	-	-	-	100kA	100kA	100kA	100kA	100kA
	50A	-	-	-	-	-	-	100kA	100kA	100kA	100kA
	63A	-	-	-	-	-	-	-	100kA	100kA	100kA

		Fuse upstream									
		aM type									
m.c.b. downstream		≤20A	25A	32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C curve	10A	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	16A	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	20A	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	25A	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA	100kA
	32A	-	-	-	-	100kA	100kA	100kA	100kA	100kA	100kA
	40A	-	-	-	-	-	100kA	100kA	100kA	100kA	100kA
	50A	-	-	-	-	-	-	100kA	100kA	100kA	100kA
	63A	-	-	-	-	-	-	-	100kA	100kA	100kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.



# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*:

Back-up protection between modular circuit-breakers, three-phase network (+ neutral) 230 / 240 V~ according to IEC/EN 60947-2:

		m.c.b. upstream				
		DX <sup>3</sup> 50kA				
		B, C and et D Curves				
m.c.b. downstream		≤25A	32A	40A	50A	63A
DX <sup>3</sup> 36kA C Curve	≤6A	85kA	85kA	72kA	72kA	72kA
	10A	85kA	85kA	72kA	72kA	72kA
	16A	85kA	85kA	72kA	72kA	72kA
	20A	85kA	85kA	72kA	72kA	72kA
	25A	-	85kA	72kA	72kA	72kA
	32A	-	-	72kA	72kA	72kA
	40A	-	-	-	72kA	72kA
	50A	-	-	-	-	72kA
	63A	-	-	-	-	-

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

Back-up protection between modular circuit-breakers and M.C.C.B., three-phase network (+ neutral) 230 / 240 V~ according to IEC/EN 60947-2:

		m.c.c.b. upstream										
		DPX <sup>3</sup> 160 / DPX <sup>3</sup> 160 + diff.								DPX 250ER		
		50kA								50kA		
m.c.b. downstream		16A	25A	40A	63A	80A	100A	125A	160A	100A	160A	250A
DX <sup>3</sup> 36kA C curve	≤6A	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	10A	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	16A		75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	20A		75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	25A			75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	32A			75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	40A				75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	50A				75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	63A					75kA	75kA	75kA	75kA	75kA	75kA	75kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*:

Back-up protection between modular circuit-breakers and M.C.C.B., three-phase network (+ neutral) 230 / 240 V~ according to IEC/EN 60947-2:

		m.c.c.b. upstream									
		DPX <sup>3</sup> 250 / DPX <sup>3</sup> 250+diff.				DPX-L 250					
		70kA				100kA					
m.c.b. downstream		100A	160A	200A	250A	25A	40A	63A	100A	160A	250A
DX <sup>3</sup> 36kA C curve	10A	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	16A	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	20A	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA	75kA
	25A	75kA	75kA	75kA	75kA	-	75kA	75kA	75kA	75kA	75kA
	32A	75kA	75kA	75kA	75kA	-	75kA	75kA	75kA	75kA	75kA
	40A	75kA	75kA	75kA	75kA	-	-	75kA	75kA	75kA	75kA
	50A	75kA	75kA	75kA	75kA	-	-	75kA	75kA	75kA	75kA
	63A	75kA	75kA	75kA	75kA	-	-	-	75kA	75kA	75kA

		m.c.c.b. upstream					
		DPX-L 630MT					
		100kA					
m.c.b. downstream		250A	320A	400A	500A	630A	250A
DX <sup>3</sup> 36kA C curve	10A	75kA	75kA	75kA	75kA	75kA	75kA
	16A	75kA	75kA	75kA	75kA	75kA	75kA
	20A	75kA	75kA	75kA	75kA	75kA	75kA
	25A	75kA	75kA	75kA	75kA	75kA	75kA
	32A	75kA	75kA	75kA	75kA	75kA	75kA
	40A	75kA	75kA	75kA	75kA	75kA	75kA
	50A	75kA	75kA	75kA	75kA	75kA	75kA
	63A	75kA	75kA	75kA	75kA	75kA	75kA

All these values are also valid for circuit breakers associated to differential blocks.

According to the curves and ratings of circuit breakers, attention to the magnetic threshold and to the size of upstream circuit breakers which must necessarily be higher.

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*

### Selectivity between two levels of protection

- . The downstream circuit breaker must always have a magnetic threshold and a rated current lower than those of the upstream protection.
- . Selectivity is indicated total (T) if there is selectivity up to the value of breaking capacity (according to IEC / EN 60947-2) of the downstream circuit breaker.

### Selectivity between modular circuit breakers and fuses:

- . Selectivity limit at 400V~: values in Ampere.

		Fuse upstream							
		gG type							
m.c.b. downstream		32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C curve	10A	-	1600	2200	3200	3600	7000	11000	20000
	16A	-	1400	1800	2600	3000	5600	8000	15000
	20A	-	1200	1500	2200	2500	4600	6300	10000
	25A	-	-	1300	2000	2200	4100	5500	9000
	32A	-	-	1200	1700	1900	3500	4500	8000
	40A	-	-	-	-	1700	3000	4000	6000
	50A	-	-	-	-	1600	2600	3500	5000
63A	-	-	-	-	-	2400	3300	5000	

		Fuse upstream								
		aM Type								
m.c.b. downstream		25A	32A	40A	50A	63A	80A	100A	125A	160A
DX <sup>3</sup> 36kA C Curve	10A	-	1100	1700	2500	5000	7800	12000	25000	30000
	16A	-	1000	1400	2100	4000	6000	9000	21000	25000
	20A	-	-	1300	1800	3400	5100	7000	14000	20000
	25A	-	-	1100	1600	3000	4500	6000	9300	14000
	32A	-	-	-	1300	2400	3800	5000	7700	9000
	40A	-	-	-	-	2100	3100	4200	6400	7000
	50A	-	-	-	-	2000	2900	3700	6000	6000
63A	-	-	-	-	-	2800	3500	5500	6000	

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*

### Selectivity between modular circuit breakers:

. Selectivity limit at 400V~: values in Ampere.

		m.c.b. upstream							
		DX <sup>3</sup> 50kA							
		C Curve							
m.c.b. downstream		10	16	20	25	32	40	50	63
DX <sup>3</sup> 36kA C Curve	10A	-	120	150	210	500	700	1000	1800
	16A	-	-	150	187	300	500	700	1300
	20A	-	-	-	187	300	400	500	1000
	25A	-	-	-	-	240	400	500	800
	32A	-	-	-	-	-	300	500	600
	40A	-	-	-	-	-	-	400	600
	50A	-	-	-	-	-	-	-	500
	63A	-	-	-	-	-	-	-	-

		m.c.b. upstream							
		DX <sup>3</sup> 50kA							
		D Curve							
m.c.b. downstream		10	16	20	25	32	40	50	63
DX <sup>3</sup> 36kA C Curve	10A	-	192	240	300	500	700	1000	1800
	16A	-	-	240	300	384	500	700	1300
	20A	-	-	-	300	384	480	600	1000
	25A	-	-	-	-	384	480	600	800
	32A	-	-	-	-	-	480	600	756
	40A	-	-	-	-	-	-	600	756
	50A	-	-	-	-	-	-	-	756
	63A	-	-	-	-	-	-	-	-

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*

### Selectivity between modular circuit breakers and M.C.C.B.s:

. Selectivity limit at 400V~: values in Ampere.

		m.c.c.b. upstream					
		DPX 125					
		16 – 25 – 36 kA					
m.c.b. downstream		16A	25A	40A	63A	100A	125A
DX <sup>3</sup> 36kA C Curve	10A	5000	5000	5000	5000	7500	7500
	16A	-	4000	4000	4000	6000	6000
	20A	-	4000	3000	3000	5000	5000
	25A	-	-	3000	3000	4500	4500
	32A	-	-	-	2000	4000	4000
	40A	-	-	-	2000	3000	3000
	50A	-	-	-	-	3000	3000
	63A	-	-	-	-	3000	3000

		m.c.c.b. upstream												
		DPX <sup>3</sup> 160E / B / N DPX <sup>3</sup> 160E / B / N + diff.								DPX 160				
		16 - 25 - 50kA								25 – 36 – 50kA				
m.c.b. downstream		16A	25A	40A	63A	80A	100A	125A	160A	25A	40A	63A	100A	160A
DX <sup>3</sup> 36kA C Curve	10A	T	T	T	T	T	T	T	T	7000	7000	7000	7000	T
	16A	-	T	T	T	T	T	T	T	6000	6000	6000	6000	18000
	20A	-	-	T	T	T	T	T	T	-	5000	5000	5000	12000
	25A	-	-	36000	T	T	T	T	T	-	3500	3500	4000	8500
	32A	-	-	-	T	T	T	T	T	-	-	2000	3500	7000
	40A	-	-	-	T	T	T	T	T	-	-	2000	2500	6000
	50A	-	-	-	-	4000	5000	10000	10000	-	-	-	2000	5500
	63A	-	-	-	-	-	5000	10000	10000	-	-	-	2000	5000

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 5. GENERAL CHARACTERISTICS *(continued)*

### Selectivity between modular circuit breakers and M.C.C.B.s:

. Selectivity limit at 400V~: values in Ampere.

		m.c.c.b. upstream												
		DPX 250ER			DPX 250 / H / L						DPX <sup>3</sup> 250 DPX <sup>3</sup> 250 + diff.			
		25 - 36 - 50kA			25 - 70 - 100kA						25 - 36 - 70kA			
m.c.b. downstream		100A	160A	250A	25A	40A	63A	100A	160A	250A	100A	160A	200A	250A
DX <sup>3</sup> 36kA C Curve	10A	T	T	T	5000	5000	5000	15000	T	T	T	T	T	T
	16A	8000	T	T	4000	4000	4000	10000	T	T	T	T	T	T
	20A	6000	T	T	-	4000	4000	8000	T	T	T	T	T	T
	25A	5000	8500	T	-	3000	3000	6000	T	T	T	T	T	T
	32A	4000	7000	T	-	-	2000	5000	T	T	T	T	T	T
	40A	3500	6000	T	-	-	2000	5000	10000	T	T	T	T	T
	50A	3000	5500	7000	-	-	-	4000	8000	T	20000	T	T	T
63A	2000	5000	5000	-	-	-	4000	8000	T	15000	T	T	T	

		m.c.c.b. upstream							
		DPX 400AB		DPX 630 / H / L					
		36kA		36 - 70 - 100kA					
m.c.b. downstream		320A	400A	250A	320A	400A	500A	630A	250A
DX <sup>3</sup> 36kA C Curve	10A	36000	36000	T	T	T	T	T	T
	16A	36000	36000	T	T	T	T	T	T
	20A	36000	36000	T	T	T	T	T	T
	25A	36000	36000	T	T	T	T	T	T
	32A	36000	36000	T	T	T	T	T	T
	40A	36000	36000	T	T	T	T	T	T
	50A	36000	36000	T	T	T	T	T	T
63A	36000	36000	T	T	T	T	T	T	

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 6. CONFORMITIES AND APPROVALS

### Compliance to standards:

- . Standard reference: IEC/EN 60947-2 with 36 kA breaking capacity
- . CEE guidelines : 73/23/CEE + 93/68/CEE
- . Legrand circuit-breakers can be used under the conditions of use as defined by IEC / EN 60947.
- . The performance of circuit breakers can be influenced by particular climates: hot dry, cold dry, hot humid, salt fog atmosphere

### Classification according to Annex Q (standard IEC/EN 60947-1) :

- . Category C with a range test temperature -25 °C / +70 °C
- . salt fog atmosphere according IEC 60068-2-52

### Environment respect – Compliance with CEE directives:

- . Compliance with Directive 2002/95/EC of 27/01/03 called "RoHS" which provides for the banning of hazardous substances such as lead, mercury, cadmium, hexavalent chromium, brominated flame retardants polybrominated biphenyls (PBBs) and polybrominated diphenyl ethers (PBDEs) from 1<sup>st</sup> July 2006
- . Compliance with Directive 91/338/CEE of 18/06/91 and Decree 94-647 of 27/07/04

### Plastic materials :

- . Halogens-free plastic materials.
- . Marking of parts according to ISO 11469 and ISO 1043.

### Packaging:


- . Design and manufacture of packaging in accordance with Decree 98-638 of 07.20.98 and Directive 94/62/EC

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 7. CHARACTERISTIC CURVES

Limiting current curve: circuit breakers C curve



. Icc = Square value of symmetric component of the short circuit current ( kA ).  
 . IP = Max peak value ( kA )




# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40


## 7. CHARACTERISTIC CURVES (continued)

Operating characteristic of circuit breakers C curve :



**7. CHARACTERISTIC CURVES** *(continued)*

. Limiting thermal energy curve of circuit breakers C curve, 2P (230V~ / 50Hz) :




.  $I_{cc}$  = Square value of symmetric component of the short circuit current ( kA ).  
 .  $I^2t$  = Thermal energy limited (A<sup>2</sup>s).

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 7. CHARACTERISTIC CURVES *(continued)*

. Limiting thermal energy curve of circuit breakers C curve, 2P (400V~ / 50Hz) :



.  $I_{cc}$  = Square value of symmetric component of the short circuit current ( kA ).


.  $I^2t$  = Thermal energy limited (A<sup>2</sup>s).

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 7. CHARACTERISTIC CURVES (continued)

. Limiting thermal energy curve of circuit breakers C curve, 1P / 3P / 4P (400V~ / 50Hz) :



.  $I_{cc}$  = Square value of symmetric component of the short circuit current ( kA ).

.  $I^2t$  = Thermal energy limited (A<sup>2</sup>s).

# DX<sup>3</sup> MCB 36kA up to 63A (1,5 modules per pole)

Cat. N°(s): 4 100 07 to 14, 4 10 20 to 27, 4 100 33 to 40

## 8. AUXILIARIES AND ACCESSORIES

### Add-on modules 63A:

mcb	Add on module		
	2P	3P	4P
2P	X	-	-
3P	-	X	-
4P	-	-	X

### Wiring accessories:

- . Sealable screw cover (cat n° 4 063 06).
- . Insulating shields (cat n° 4 063 12)

### Signal auxiliaries:

- . Auxiliary contact (½ module – cat n° 4 062 58).
- . Fault signalling changeover switch (½ module – cat n° 4 062 60).
- . Auxiliary contact modifiable in default signal (½ module – cat n° 4 062 62).
- . Auxiliary contact + fault signalling switch - can be modified to 2 auxiliary contacts (1 module - cat n° 4 062 66).

### Control auxiliaries:

- . Shunt releases (1 module - cat n° 4 062 76 / 78).
- . Under voltage release (1 module - cat n° 4 062 80 / 82).
- . Autonomous shunt trip for NC push-button (1 module - cat n° 4 062 84).

### Possible combinations of m.c.b and auxiliaries:

- . Auxiliaries are clipped on the left of the m.c.b.
- . Maximum number of auxiliaries for one circuit-breaker: 3.
- . Two signalling auxiliaries max. (cat. n° 4 062 58 / 60 / 62 / 66).
- . Only one control auxiliary (cat. n° 4 062 76 / 78 / 80 / 82 / 84).
- . One remote control or Stop & Go motor driven remote control
- . If signalling and control auxiliaries are associated on the same circuit breaker, the command auxiliary must be placed to the left of the signal auxiliary (ref. 4 062 5x / 6x).

### Sealing:

- . Possible in "Open" mode (OFF) or "Close" mode (ON).

### Lockout:

- . By padlock (using ref. 4 063 13 or 0 227 97), whit support for padlock (using ref. 4 063 03) in "Open" mode (OFF).

### Installation software:

- . XL PRO<sup>3</sup>