



## 5. TECHNICAL CHARACTERISTICS

### ■ 5.1 Mechanical characteristics

Impact tests: IK 02

Protection against solid bodies and liquids: IP 40

### ■ 5.2 Material characteristics

Thermoplastic with glossy finish (White, Ivory)

Colour: White T084: PC

Ivory: PC

Dark Grey: PC painted

Brown: PC painted

Halogen free

UV resistant

Self-extinguishing: 650° C / 30 s

### ■ 5.3 Electrical characteristics

Contact blades gold plated on nickel (gold thickness: 50 V")

Spring shutter obturation when socket not in use

Plug retention in socket: 5.3 kg (53 Newtons)

### ■ 5.4 Climatic characteristics

Storage temperature: - 10° C to + 70° C

Operating temperature: - 5° C to + 35° C

## 6. CLEANING

Surface cleaning with a soft, slightly damp cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products.

**Caution:** A preliminary test should be carried out if other specific cleaning products are to be used.

## 7. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing.

See e.catalogue.