


Arteor™
TV/R/SAT sockets

Cat. No(s): 5 721 72 - 5 726 72/90/91




1. USE

TV/R/SAT: for receiving TV, Radio and Satellite signals.
 UHD (Ultra High Definition) compatible.
 DAB+ (Digital Audio Broadcasting) Radio.
 Class A shielded star sockets LTE Ready (4G protected).
 Recommended coaxial cable 17/19 VATC.
 Single cable entry.
 Can be flush mounted in a box min. 40 mm deep.
 To be equipped with plate.

2. RANGE


Description	White	Magne-sium	Soft Alu	Champagne
TV/R/SAT socket FM radio + DAB+ 2 modules	5 721 72	5 726 72	5 726 90	5 726 91

3. DIMENSIONS (mm)





A	B	C	D
45	45	39.5	11.5

4. CONNECTION



5. WIRING PRECAUTIONS



By restricting deformation of the coaxial cable, the rear connection avoids impedance discontinuity, thereby sustaining performance.

6. TECHNICAL CHARACTERISTICS

■ 6.1 Mechanical characteristics

Protection against impacts: IK 03
Protection against solid/bodies and liquids: IP 21
Cable resistance: 120 N

■ 6.2 Material characteristics

Cover plate: ABS
White RAL 9003
Painted Magnesium - Soft Alu - Champagne

Halogen-free
UV-resistant

Motor:

Box: Zamac
Cover: Zamac
Pin: Bronze
Screws: Steel

Self-extinguishing:

850°C/30 s for insulating parts holding live parts in place.
650°C/30 s for other parts made of insulating materials.

■ 6.3 Electrical characteristics

- Male connector Ø 9.52 mm (TV)
- Female connector (Radio)
- Female F screw-type connector (SAT)

Characteristic impedance: 75 ohm
Class A shielding efficiency (class A shielding is necessary to prevent interference caused by using new 3 and 4 G phone signals, as these unwanted signals can result in pixellation on screen or adversely affect the sound track).

Frequency bands: TV: 5-68 / 120-862 MHz
R: 87.5-108 MHz MF / 174 - 223 MHz DAB+
SAT: 950-2400 MHz

Attenuation : < 1.5 dB maximum

■ 6.4 Climate characteristics

Storage temperature: -10°C to +70°C
Usage temperature: -5°C to +35°C

7. CLEANING

Surface cleaning with a cloth.
Do not use acetone, tar remover, trichloroethylene.




Resistant to the following products: Hexane (NF C 61-314), Methylated spirit, soapy water, diluted ammonia, bleach diluted to 10 %, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using other special cleaning products.

8. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards.
See e-catalogue.

9. PERFORMANCES



DAB Radio TV sockets

