


SPD classification according to EN 61643-11 within 5M	Type 1 + Type 2 + Type 3	
SPD classification according to IEC 61643-11 within 5M	Class I + Class II + Class III	
Nominal operating voltage	Un	230/400VAC
Max. continuous operating voltage	Uc	275VAC
Lightning impulse current (10/350μs)	Iimp	25kA
Nominal discharge current (8/20μs)	In	25kA
Max. discharge current (8/20μs)	Imax	100kA
Combined impulse	Uoc	20kV
Voltage protection level (max.)	Up	≤1.3kV
Max. backup fuse		315A gG
Response time	tA	≤25ns
Operating temperature range	Tu	-40°C-80°C
Operating state/fault indication		green/red
Cross-section area (Min.)		4mm <sup>2</sup>
Cross-section area (Max.)		35mm <sup>2</sup>
For mounting on		35mm DIN rail
Enclosure material		UL94-V0
Degree of protection		IP20

Made in P.R.C.

[www.traconelectric.com](http://www.traconelectric.com)

HU Más nyelvek elérhetőek a weboldalunkon.  
DE Weitere Sprachen finden Sie auf unserer Website.  
SK Ostatné jazyky sú k dispozícii na našej webových stránke.  
RO Alte limbi sunt disponibile pe site-ul nostru.  
PL Inne języki są dostępne na naszej stronie internetowej.  
SI Drugi jeziki so na voljo na naši spletni strani.



RS Ostali jezici su dostupni na našoj veb stranici.  
CZ Další jazyky jsou k dispozici na našich webových stránkách.  
HR Ostali jezici dostupni su na našoj web stranici.  
IT Altre lingue sono disponibili sul nostro sito web.  
FR D'autres langues sont disponibles sur notre site Internet.  
ES Otros idiomas están disponibles en nuestro sitio web.



Tracon Budapest Kft  
H-2120 Dunakeszi, Pallag u. 23.