

PRODUCT DATASHEET P PAR 38 13 W/ E27

PARATHOM PAR38 | LED reflector lamps PAR38 with retrofit screw base



AREAS OF APPLICATION

- Display cabinets and shop windows
- Museums, art galleries
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Very long lifetime of up to 25,000 h
- Low energy consumption
- Easy relamping thanks to compact design
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- Professional LED alternative to PAR38 halogen lamps
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Rated wattage	13.00 W
Nominal wattage	13.00 W
Nominal voltage	220240 V
Max. lamp no. on circuit break. 10 A (B)	31
Max. lamp no. on circuit break. 16 A (B)	50
Operating frequency	5060 Hz
Power factor λ	> 0.50

Photometrical data

Nominal luminous flux	300 lm
Rated luminous flux	300 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Green
Luminous flux	300 lm
Color rendering index Ra	-

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	134.0 mm
Diameter	122.0 mm
Outer bulb	PAR121
Length	134.0 mm
Maximum diameter	122.0 mm

Temperatures & operating conditions

Maximum temperature at tc test point	75 °C

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Show WEEE picto	Yes	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy consumption	13 kWh/1000h
Energy consumption	13 KWII/1000II

Country-specific categorizations

Order reference LPPAR38 13	W 230
----------------------------	-------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075117174	Folding carton box 1	127 mm x 129 mm x 170 mm	465.00 g	2.79 dm³
4058075117181	Shipping carton box 6	402 mm x 278 mm x 196 mm	2965.00 g	21.90 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.