

0026651	DATA SHEET	
Valid from: 12.07.2018	ÖLFLEX® FD 90 CY	

Application

ÖLFLEX® FD 90 CY cables are **DESINA®** compliant screened high-flexible, sheathed cables for the European, North American and Canadian market.

They are designed for flexible use as well as for fixed installation subject to medium mechanical load conditions.

They are also suitable for use in dry, damp or wet areas. If using outdoors, observe the indicated temperature range and use with UV protection.

ÖLFLEX® FD 90 CY cables are suitable for linear, automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

The screening braid protects against interference from electrical fields.

Application range: In power chains or moving machine parts, for internal wiring of electric and electronic equipment in switch cabinets, specially designed for power circuits of servomotors driven by frequency converters, this cable can substitute screened multi-core motor cables where space requirements or minimum bending radii cause problems, test systems in the automotive industry, vehicles and stationary fuel cell systems

USE acc. to UL: PVC sheathed cable for internal wiring or external interconnection of electronic equipment.

Appliances where exposed to oil at a temperature not exceeding 80° C.

USE acc. to CSA: Cables for internal wiring or external interconnection with or without mechanical abuse.

Design

Design	according to UL AWM Style 10107 based on VDE 0250
Approvals	UL AWM Style 10107 (File No. E63634) ≤120 mm ² CSA AWM I A/B, II A/B ≥150 mm ² cUL AWM I A/B, II A/B
Conductor	extra fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, min. Class 6
Core insulation	PVC compound (UL/CSA 90°C rating)
Core identification	BK or GN/YE
Taping	non-woven wrapping
Screen	braid of tinned copper wires, coverage = 85% (nominal value)
Outer sheath	PVC compound (UL/CSA 90°C rating) colour: Orange, similar RAL 2003


Electrical properties

Specific insulation resistance (20°C)	> 20 G Ω x cm
Nominal voltage	IEC U ₀ / U: 600 / 1000 V UL/CSA 600 V
Test voltage	4000 V AC

Mechanical and thermal properties

Min. bending radius	flexing: up from 7.5 x cable diameter fixed installation: 3 x cable diameter
Bending cycles and power chain operation parameters	See Selection Table A2-1 in the appendix of our online catalogue For use in power chains: Please comply with assembly guideline Appendix T3

Creator: LABU/PDC Released: HAPF/PDC	Document: DB0026651EN Version: 08	Page 1 of 2
---	--------------------------------------	-------------

0026651	DATA SHEET	
Valid from: 12.07.2018	ÖLFLEX® FD 90 CY	

Temperature range	flexing (VDE): -5 °C up to +70 °C max. conductor temp. flexing (UL/CSA): -5 °C up to +90 °C max. conductor temp. fixed installation(VDE): -40 °C up to +80 °C max. conductor temp. fixed installation (UL/CSA): up to +90 °C max. conductor temp.
Flammability	flame retardant in acc. with IEC 60332-1-2 resp. VDE 0482-332-1-2 UL: Vertical flame test VW-1, FT2 CSA: FT1
Oil resistance	acc. to EN 50363-4-1 resp. VDE 0207-363-4-1, TM5 UL: 80°C rating acc. to UL 758 CSA: CSA C22.2 No. 210-15
Tests	acc. to IEC 60811 resp. VDE 0473-811, VDE 0472, EN 50395, EN 50396 UL 1581 and CSA C22.2
EU Directives	These cables are conform to the EU-Directives 2014/35/EU (Low Voltage Directive)

Creator: LABU/PDC Released: HAPF/PDC	Document: DB0026651EN Version: 08	Page 2 of 2
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.