


55502460	DATA SHEET	
Valid from: 03.07.2018	SILVYN® MPC-M	

The SILVYN® MPC M is a polyamide conduit gland for smooth and corrugated conduits. The hexagonal body with integrated conduit connection enables best assembling.



Material: PA 66

Features: Dust protection
Moisture protection
Tensile strength

Resistance: To oil

Temperature range: -40°C up to +120°C

Colour: Black (UV-Resistant)
Grey (RAL 7001)

Norm Reference:




Notes: Free of halogen, Phosphor and Sulphur

Protection class: IP 65 up to IP 68

Dimensions table:

Part No.	Part name	Total length mm	Smallest inner Ø mm	Largest outer Ø mm	Length of thread mm	SW
black						
5550 2460	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2461	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2462	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2463	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2464	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2465	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2469	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2466	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2467	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2468	SILVYN® MPC-M 63x1,5	56	48	76	16	73
grey						
5550 2441	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2442	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2443	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2444	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2445	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2446	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2447	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2448	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2449	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2439	SILVYN® MPC-M 63x1,5	56	48	76	16	73

Creator: M. Auch /PDP Released: DAMU1/PDP	Document: DB55502460EN Version: 04	Page 1 of 2
--	---------------------------------------	-------------

55502460	DATA SHEET	
Valid from: 03.07.2018	SILVYN® MPC-M	

Suitable:

SILVYN® SI
 SILVYN® SP
 SILVYN® SP-PU
 SILVYN® EL waved/smooth
 SILVYN® ELU waved/smooth
 SILVYN® ELÖ waved/smooth
 SILVYN® ELT waved/smooth
 SILVYN® ELR smooth

Allocation table:

Conduit	 SILVYN® SI	 SILVYN® SP/ SP-PU	 SILVYN® EL/ELÖ/ELT/ELR/ELU
SILVYN® MPC-M 16x1,5/1	11x14		12
SILVYN® MPC-M 16x1,5/2	13x16	12x16	16
SILVYN® MPC-M 20x1,5/1	13x16	12x16	16
SILVYN® MPC-M 20x1,5/2		16x20	20
SILVYN® MPC-M 25x1,5		22x27	25
SILVYN® MPC-M 32x1,5/1			30
SILVYN® MPC-M 32x1,5/2			32
SILVYN® MPC-M 40x1,5			40
SILVYN® MPC-M 50x1,5			50
SILVYN® MPC-M 63x1,5		49x56	63

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Auch /PDP Released: DAMU1/PDP	Document: DB55502460EN Version: 04	Page 2 of 2
--	---------------------------------------	-------------