

55501400	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LKI-M / LKI	

The SILVYN® LKI-M (metric thread) and LKI (PG thread) is a one part connector body which is made of polypropylene, with a turn able connecting thread. The connector has a hexagonal wrench surface and an integrated ferrule and can be used in machine and plant constructions.



Material: Body – Polypropylene
Ferrule – Polypropylene

Features: Simple and easy assembling
Vibration proof and tension proof
Conduit screw-out-locking

Resistance: To gas, oil, fat, alkalises, acids,
bases and common solvents

Temperature range -10°C up to +110°C

Colour: Grey



Norm Reference:

Notes: Free of halogen and Phosphor
Self-extinguishing HB in acc. to UL 94

Protection class: IP 65 acc. EN 60529



Dimensions table:



Part No.	Part name	Nominal Ø mm	inner Ø mm	outer Ø mm	Length of thread mm	Total length mm	SW
SILVYN® LKI-M							
5550 1400	SILVYN® LKI-M 12x1,5	10	5,5	17,5	10	38	16
5550 1410	SILVYN® LKI-M 16x1,5	14	9,5	21	10	39,5	19
5550 1420	SILVYN® LKI-M 20x1,5	17	11,5	24,5	10	42	22
5550 1430	SILVYN® LKI-M 25x1,5	21	14,5	30	11	48	27
5550 1440	SILVYN® LKI-M 32x1,5	27	19,5	39	12	58	35
5550 1450	SILVYN® LKI-M 40x1,5	36	27	50	12	59	45
5550 1460	SILVYN® LKI-M 50x1,5	45	35,5	59,5	12	62,5	54
5550 1470	SILVYN® LKI-M 63x1,5	56	46	71,5	15	68	65
SILVYN® LKI							
5500 0000	SILVYN® LKI 7	10	5,5	17,5	10	38	16
5500 0010	SILVYN® LKI 9	14	9,5	21	10	39,5	19
5500 0020	SILVYN® LKI 11	17	11,5	24,5	10	42	22
5500 0030	SILVYN® LKI 13,5	19	13	26,5	10	42	24
5500 0040	SILVYN® LKI 16	21	14,5	30	11	48	27
5500 0050	SILVYN® LKI 21	27	19,5	39	11	58	35
5500 0060	SILVYN® LKI 29	36	27	50	12	59	45
5500 0070	SILVYN® LKI 36	45	35,5	59,5	12	62,5	54
5500 0090	SILVYN® LKI 48	56	46	71,5	15	68	65

55501400	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LKI-M / LKI	

Suitable Conduit: SILVYN® FPS
SILVYN® FD-PU

Allocation table:

Description	 SILVYN® FPS	 SILVYN® FD-PU
SILVYN® LKI-M 12x1,5	SILVYN® FPS 7x10	SILVYN® FD-PU 7x10
SILVYN® LKI-M 16x1,5	SILVYN® FPS 10x14	SILVYN® FD-PU 10x14
SILVYN® LKI-M 20x1,5	SILVYN® FPS 13x17	SILVYN® FD-PU 13x17
SILVYN® LKI-M 25x1,5	SILVYN® FPS 16x21	SILVYN® FD-PU 16x21
SILVYN® LKI-M 32x1,5	SILVYN® FPS 22x27	SILVYN® FD-PU 22x27
SILVYN® LKI-M 40x1,5	SILVYN® FPS 29x36	SILVYN® FD-PU 29x36
SILVYN® LKI-M 50x1,5	SILVYN® FPS 38x45	SILVYN® FD-PU 38x45
SILVYN® LKI-M 63x1,5	SILVYN® FPS 48x56	SILVYN® FD-PU 48x56

Description	 SILVYN® FPS	 SILVYN® FD-PU
SILVYN® LKI 7	SILVYN® FPS 7x10	SILVYN® FD-PU 7x10
SILVYN® LKI 9	SILVYN® FPS 10x14	SILVYN® FD-PU 10x14
SILVYN® LKI 11	SILVYN® FPS 13x17	SILVYN® FD-PU 13x17
SILVYN® LKI 13,5	SILVYN® FPS 15x19	SILVYN® FD-PU 15x19
SILVYN® LKI 16	SILVYN® FPS 16x21	SILVYN® FD-PU 16x21
SILVYN® LKI 21	SILVYN® FPS 22x27	SILVYN® FD-PU 22x27
SILVYN® LKI 29	SILVYN® FPS 29x36	SILVYN® FD-PU 29x36
SILVYN® LKI 36	SILVYN® FPS 38x45	SILVYN® FD-PU 38x45
SILVYN® LKI 48	SILVYN® FPS 48x56	SILVYN® FD-PU 48x56

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55501400EN Version: 02	Page 2 of 2
---	---------------------------------------	-------------