


1550556	DATA SHEET	
valid from: 2021-10-20	N2XH-J, N2XH-O	

Application

N2XH-J, N2XH-O are halogen free, highly flame retardant power cables for installation indoors, in the air or concrete. For outdoor use the cable should be protected against sunlight and the temperature range should be considered. Not intended for direct-buried installations or in water. Strains of more than 15 N/mm² are not allowed.

Application range:

Especially for use in power stations, in transformer stations and for power supply and particularly where human life as well as valuable property are exposed to high risk of fire hazards.

Design

Design	acc. to DIN VDE 0276-604 (VDE 0276-604)
Certification	The cable is marked with the $\triangleleft VDE \triangleright$ HAR-sign or HAR-identification thread. Classification of fire behaviour according to EN 13501-6 and EN 50575 (article/dimension range see www.lappkabel.com/cpr)
Conductor	single or multi-wire, bare copper wire conductor acc. IEC 60228 resp. EN 60228 (VDE 0295), class 1 or 2
Insulation	irradiated Polyethylene compound 2X11 acc. to VDE 0276-604 (VDE 0276-604)
Core identification code	colour-coded acc. to VDE 0293-308 (VDE 0293-308)
Outer sheath	halogen free, thermoplastic Polyolefin-compound HM4 acc. to VDE 0276-604 (VDE 0276-604) colour: black

Electrical properties at 20 °C

Nominal voltage	U ₀ /U: 600/1000 V
Test voltage	C / C: 4000 V AC

Mechanical and thermal properties

Minimum bending radius	single core: 15 x outer diameter multi core: 12 x outer diameter
Temperature range	During installation: -5 °C up to + 90 °C Fixed installation: -40 °C up to +90 °C max. conductor temperature
Flammability	Flame retardant acc. IEC 60332-1-2 resp. EN 60332-1-2 (VDE 0482-332-1-2) No Flame propagation acc. IEC 60332-3-24 resp. EN 60332-3-24 (VDE 0482-332-3-24)
Halogen free	acc. to IEC 60754-1 resp. EN 50267-2-1 (VDE 0482-267-2-1)
Corrosivity of gases	acc. to IEC 60754-2 resp. EN 50267-2-2 (VDE 0482-267-2-2)
Smoke density	acc. to EN 61034 (VDE 0482-1034)
Ozone resistance	acc. to EN 50396 (VDE 0473-396)

Tests acc. to IEC 60811, EN 50395, EN 50396

General requirements These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)
These cables (see www.lappkabel.com/cpr) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Note Trade product, no Lapp product

Creator: PESA / PDC	Document: DB1550556EN	Page 1 of 1
Released: ALTE / PDC	Version: 06	