


1136752	DATA SHEET	
valid from: 01.01.2019	ÖLFLEX® CLASSIC 115 CY	

Application

ÖLFLEX® CLASSIC 115 CY cables are control cables for occasional flexible use and fixed installation under medium mechanical load conditions. They are also suitable for use in dry, damp or wet areas. If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature.

ÖLFLEX® CLASSIC 115 CY cables are suitable for occasional, non-automated movements. They meet the requirements for slow rotational movements, such as in the loop of a wind turbine. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

The screening braid protects against interference from electrical fields.

Application range:

Control units for machine tools, conveyor systems, measurement and control technology, office machines and systems for data processing. This cable is suitable for torsion application in wind turbines (WTG). The torsional load is limited to applications, as they typically occur in the loop of a wind turbine.

Design

Design	based on EN 50525-2-5 1 resp. VDE 0285-525-2-5 1
Conductor	bare copper, fine wire strand in acc. to IEC 60228 resp. VDE 0295, class 5
Insulation	PVC compound T12 acc. to DIN EN 50363-3 resp. VDE 0207-363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to DIN EN 50334 resp. VDE 0293-334
Stranding	cores are stranded in layers
Taping	plastic foil
Screen	braid of tinned copper, coverage = 85% (nominal value)
Outer sheath	PVC compound TM2 acc. to DIN EN 50363-4-1 resp. VDE 0207-363-4-1, with increased requirements acc. to Lapp specifications Colour: Silver grey, similar RAL 7001

Electrical properties at 20°C

Specific volume resistivity	> 20 G Ω x cm
Transfer impedance	max. 250 mΩ/m (at 30 MHz)
Rated voltage	U ₀ / U: 300 / 500 V
Test voltage	core / core: 4000 V AC core / screen: 2000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x cable diameter fixed installation: 6 x cable diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
Torsional stress	in WTG: TW-0 (5.000 cycles at ≥ + 5 °C) TW-1 (2.000 cycles at ≥ -20 °C) ± 150° /m at 1 revolution per minute
Flammability	acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2
Tests	acc. to IEC 60811, EN 50395, EN 50396
General requirements	This cable is conform to the EU-Directives 2014/35/EU (Low Voltage Directive)

Creator: HESC / PDC	Document: DB1136752EN	Page 1 of 1
Released: ALTE / PDC	Version: 07	