


1119809	<b>DATA SHEET</b>	
valid from: 10.11.2020	<b>ÖLFLEX® CLASSIC 110 [black]</b>	

## Application

ÖLFLEX® CLASSIC 110 [black] cables are VDE approved power and control cables for occasional flexible use and fixed installation for medium mechanical stresses. They are among others designed for use in dry, damp and wet conditions. They are suitable for outdoor use if the indicated temperature range is observed. They are largely resistant to acids, alkalis and certain oils at room temperature.

ÖLFLEX® CLASSIC 110 [black] cables are limited suitable for free and continuously recurring movements. The maximum tensile load is 15 N/mm<sup>2</sup> of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

### Application range:

As power and connecting cable for control systems in machine tools, plant engineering and construction, industrial machinery, conveyor systems, production and assembly lines as well as in measuring and control technology and data processing systems.

This cable is suitable for torsion application in wind turbines (WTG). The torsional load is limited to applications, as they typical occur in the loop of a wind turbine.

## Design

Design	based on EN 50525-2-51
Certification	< VDE-REG 7030 > limited to following dimension range: 0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> 2 - 65 cores 4 mm <sup>2</sup> - 16 mm <sup>2</sup> 2 - 7 cores 25 mm <sup>2</sup> - 120 mm <sup>2</sup> 2 - 5 cores EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see <a href="http://www.lappkabel.com/cpr">www.lappkabel.com/cpr</a> )
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. EN 60228, Class 5
Insulation	LAPP special PVC compound P8/1 T12 acc. to EN 50363-3 with increased requirements acc. to LAPP specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to EN 50334
Stranding	cores are stranded in layers
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 with increased requirements acc. to LAPP specification colour: black, similar RAL 9005


## Electrical properties at 20°C

Nominal voltage	U <sub>0</sub> / U: 300 / 500 V
Test voltage	core / core: 4000 V AC

## Mechanical and thermal properties

Minimum bending radius	occasional flexing: 10 x outer diameter fixed installation: 4 x outer diameter
Temperature range	occasional flexing: - 15 °C up to +70 °C max. conductor temp. Fixed installation: - 40 °C up to +80 °C max. conductor temp.
Bending cycles and power chain operation parameters	Power chain limited to 2-7 cores and 0.5 - 2.5 mm <sup>2</sup> Min. bending radius: 15 x outer diameter temperature range: -5 °C up to +70 °C max. conductor temp. Travelling distance up to 5 m: 0.2 ... 1 million bending cycles
Torsional stress	in WTG: TW-0 (5000 cycles at ≥ +5 °C) TW-1 (2000 cycles at ≥ -20 °C) ± 150° /m at 1 revolution per minute
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
UV resistance	acc. to EN 50525-1 cable with black sheath are suitable for permanent outdoor use. acc. to EN 50618 acc. to EN 50620 acc. to EN ISO 4892-2-2013, method A (change of colour allowed)
Oil resistance	acc. to EN 50290-2-22 TM54

Creator: ALTE / PDC	Document: DB1119809EN	Page 1 of 2
Released: HESC / PDC	Version: 04	

1119809	<b>DATA SHEET</b>	
valid from: 10.11.2020	<b>ÖLFLEX® CLASSIC 110 [black]</b>	

Tests	acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).
	A part of these cables (see <a href="http://www.lappkabel.com/cpr">www.lappkabel.com/cpr</a> ) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: ALTE / PDC	Document: DB1119809EN	Page 2 of 2
Released: HESC / PDC	Version: 04	