

# PRODUCT DATASHEET

## P CLAS A 100 11 W/2700K E27

PARATHOM Retrofit CLASSIC A | LED lamps, classic bulb shape



---

### AREAS OF APPLICATION

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

---

### PRODUCT BENEFITS

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

---

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Beam angle: up to 300°
- Not dimmable
- Base: E27
- Mercury-free lamps



- Lifetime: up to 15,000 h

**TECHNICAL DATA**

Electrical data

Rated wattage	11.00 W
Nominal wattage	11.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	58
Max. lamp no. on circuit break. 16 A (B)	94
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.50
Claimed equiv. conventional lamp power	100 W


Photometrical data

Nominal luminous flux	1521 lm
Rated luminous flux	1521 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	1521 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	105.0 mm
----------------	----------

<b>Diameter</b>	60.0 mm
<b>Outer bulb</b>	A60
<b>Length</b>	105.0 mm

#### Temperatures & operating conditions

<b>Maximum temperature at tc test point</b>	67 °C
---	-------

#### Lifespan

<b>Nominal lamp life time</b>	10000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000
<b>Lumen maintenance at end of service life</b>	0.70

#### Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Show WEEE picto</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

#### Capabilities

<b>Dimmable</b>	No
-----------------	----

#### Certificates & standards

<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	11 kWh/1000h

#### Country-specific categorizations

<b>Order reference</b>	LEDPCLA100 11W/
------------------------	-----------------

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075287242	Folding carton box 1	60 mm x 60 mm x 111 mm	49.00 g	0.40 dm <sup>3</sup>
4058075287259	Shipping carton box 10	325 mm x 136 mm x 126 mm	583.00 g	5.57 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.