

| | | |
|---------------------------|-----------------------------|---|
| 0035101 | DATA SHEET |  |
| valid from: 2021-04-06 | UNITRONIC® LiYY (TP) | |

Application

UNITRONIC® LiYY (TP) is a twisted pair data cable for low frequency applications. The cable is designed for fixed installation and for conditional flexible use. It is used in dry and damp interiors but not appropriate for outside usage. The twisted pairs with short lay lengths provides good decoupling of the conductor circuits. The cable is used for example in computer systems, instrumentation technology, office equipment and balances.

Design

| | |
|--------------------------|--|
| Design | based on standard VDE 0812 and EN 50288-7 |
| Certification | EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see www.lappkabel.com/cpr) |
| Conductor | fine wire strands of bare copper wires |
| Insulation | special PVC-based compound |
| Core identification code | acc. to DIN 47100 |
| Stranding | cores twisted to pairs, pairs are stranded in layers, wrapping with foil on the outer layer |
| Outer sheath | special PVC-based compound colour: grey (similar RAL 7032) |

Electrical properties at 20 °C

| | |
|-----------------------------|---|
| Conductor resistance | 0.14 mm ² : max. 138.0 Ω/km 0.25 mm ² : max. 79.0 Ω/km 0.34 mm ² : max. 57.0 Ω/km 0.5 mm ² : max. 39.0 Ω/km 0.75 mm ² : max. 26.0 Ω/km 1 mm ² : max. 19.5 Ω/km 1.5 mm ² : max. 13.3 Ω/km |
| Specific volume resistivity | > 20 G Ω x cm |
| Mutual capacitance | C/C: approx. 120 nF/km (at 800 Hz) |
| Inductance | approx. 0.65 mH/km |
| Maximum operating voltage | 0.14 mm ² : 350 V (not for power applications) ≥ 0.25 mm ² : 500 V (not for power applications) Must not be connected to the mains supply voltage. |
| Test voltage | 0.14 mm ² : 1200 V ≥ 0.25 mm ² : 1500 V |

Mechanical and thermal properties

| | |
|---------------------------|--|
| Minimum bending radius | occasional flexing: 10 x outer diameter fixed installation: 4 x outer diameter |
| Temperature range | flexing: - 5 °C up to +70 °C fixed installation: - 40 °C up to +80 °C |
| Flammability | flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 |
| General requirements | These cables are conform to EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and EU-Directive 2014/35/EU (Low Voltage Directive). A part of these cables (see www.lappkabel.com/cpr) are classified in accordance with the EU-Regulation no. 305/2011 (CPR). |
| Environmental information | These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS). |

| | | |
|----------------------|-----------------------|-------------|
| Creator: PESA / PDC | Document: DB0035101EN | Page 1 of 1 |
| Released: ALTE / PDC | Version: 07 | |