

# ACQUA T8

Weatherproof luminaire for T8 lamps



3 YEARS warranty



## Benefits

- For applications that require additional protection in aggressive environments with chemicals.
- Quick mounting in ceiling, wall or suspended.
- Easy maintenance and high-quality materials for a long-lasting product.

## Characteristics

IP 66
IK 03
Frequency 50/60Hz
Rated voltage 220-240V

### Mechanical characteristics

Housing	Compressed glass fiber reinforced polyester Grey RAL 7035
Diffuser	Injected polycarbonate or PMMA with UV protection
Closing clips	Polyamide 6
Gasket	Polyurethane
Gear tray	White lacquered steel plate
Cable entry	Grommet
Fixing clips	Stainless steel
Suspension triangles	Stainless steel
Chemical agents resistance	See website



### Electrical characteristics

Connection	3- pole connection strip
------------	--------------------------

### Functional characteristics

Guarantee	3 years
Fire protection	Flammability (UL94): HB Glow wire test (EN 60695-2-11): 650°C
Compliance	

## ACQUA T8

### Description

FAMILY	TUBE TYPE	DIFFUSER	ELECTRICAL VERSION	CLOSING CLIPS
> ACQUA	> 118: 1x18W > 136: 1x36W > 158: 1x58W > 218: 2x18W > 236: 2x36W > 258: 2x58W	> PC: polycarbonate > PMMA	> E: electronic (high frequency), non-dimmable ballast	> Polyamide 6

Special options under request


Ask our Sales Team for more details

> IX: stainless steel

### Operational data

Description	Order number	X	Xm	Y	Z					
		mm	mm	mm	mm	L x W x H mm	Pcs./Box	Box	Groupage Pcs./Euro pallet	Double pallet Pcs./Euro pallet
ACQUA 118 E	10038064	665	390	101	101	665 x 101 x 101	1	1.02	294	168 + 168
ACQUA 118 E PC	10038067	665	390	101	101	665 x 101 x 101	1	1.02	294	168 + 168
ACQUA 136 E	10038074	1282	800	101	101	1282 x 101 x 101	1	2.03	147	84 + 84
ACQUA 136 E PMMA	10078912	1282	800	101	101	1282 x 101 x 101	1	2.03	147	84 + 84
ACQUA 136 E PC	10038077	1282	800	101	101	1282 x 101 x 101	1	2.03	147	84 + 84
ACQUA 158 E	10038083	1578	1100	101	101	1578 x 101 x 101	1	2.49	147	84 + 84
ACQUA 158 E PMMA	10078913	1578	1100	101	101	1578 x 101 x 101	1	2.49	147	84 + 84
ACQUA 158 E PC	10038086	1578	1100	101	101	1578 x 101 x 101	1	2.49	147	84 + 84
ACQUA 218 E	10038094	665	390	145	101	665 x 145 x 101	1	1.28	210	120 + 120
ACQUA 218 E PC	10038097	665	390	145	101	665 x 145 x 101	1	1.28	210	120 + 120
ACQUA 236 E	10038107	1282	800	145	101	1282 x 145 x 101	1	2.57	105	60 + 60
ACQUA 236 E PMMA	10078914	1282	800	145	101	1282 x 145 x 101	1	2.57	105	60 + 60
ACQUA 236 E PC	10038110	1282	800	145	101	1282 x 145 x 101	1	2.57	105	60 + 60
ACQUA 258 E	10038120	1578	1100	145	101	1578 x 145 x 101	1	3.13	105	60 + 60
ACQUA 258 E PMMA	10078915	1578	1100	145	101	1578 x 145 x 101	1	3.13	105	60 + 60
ACQUA 258 E PC	10038123	1578	1100	145	101	1578 x 145 x 101	1	3.13	105	60 + 60

Please check with our Back Office to confirm logistic data



### Accessories

10103049	Suspension wire 2m hook and fastener, 1 unit <sup>1</sup>
----------	---

<sup>1</sup> 2 units required per luminaire

