



## ZALUX BASE ST

### Description

FAMILY	VERSION	LENGTH (mm)	LUMINOUS FLUX (lm)	CRI	LIGHT COLOUR (K)	DRIVER	PROFILE	CONNECTION	THROUGH WIRING
> B: ZALUX BASE	> ST: Standard	> 1.2: 1200 > 1.5: 1500	> 37: 3700 > 55: 5500	> 8: 80	> 40: 4000	> ET: non dimmable	> BPC: PC	> CG: cable gland + terminal block	> 3x1.5mm <sup>2</sup>

Special options under request

Ask our Sales Team for more details

> 3x2.5mm<sup>2</sup>


### Operational data

Description	Order number	Luminous flux (lm)	Power (W)	Efficiency (lm/W)	Colour temperature (K)	CRI
BST 1.2 37-840 ET BPC	10170844	3700	33	115	4000	> 80
BST 1.2 37-840 ET BPC 3x1.5	10170845	3700	33	115	4000	> 80
BST 1.5 55-840 ET BPC	10170846	5500	49	115	4000	> 80
BST 1.5 55-840 ET BPC 3x1.5	10170847	5500	49	115	4000	> 80

### Dimensions and logistics

Description	X	Xm	Y	Z					
	mm	mm	mm	mm	L x W x H mm	Pcs./Box	Box	Groupage Pcs./Euro pallet	Double pallet Pcs./Euro pallet
BSTP 1.2...	1213	800	76	67	1330 x 85 x 75	1	1.9	171	108 + 108
BSTP 1.5...	1493	1100	76	67	1610 x 85 x 75	1	2.3	171	108 + 108

Please check with our Back Office to confirm logistic data



### Accessories

10103049	Suspension wire 2m hook and fastener, 1 unit <sup>1</sup>
10149442	Theft protection (required for wall mounting), set for 1 luminaire
10207593	ZBWM wall mounting accessory (allows luminaire rotation), 2 pieces set
10256809	Fixing clips in stainless steel 316L, 2 units

<sup>1</sup> 2 units required per luminaire

