



Unica - 1 S.O. - 2P+E, shutters, DE - 2 m - orange

MGU3.037.61

IVI	a	ı	r	1
-----	---	---	---	---

Range	Unica
Device application	Power supply
Product or component type	Socket-outlet
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	Schuko
Outlet standard description	Side earth

Complementary

Complementary	
Cover type	With shutter
Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Orange
Connections - terminals	Screw terminals
Cable cross section	04 mm² - cable stiffness: flexible 04 mm² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 ln and 1.1 Un, cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	ASA + PC: mechanism cover
Surface finish	Brilliant

Quantity per set	Set of 1 blister
Product certifications	FR.ME63.B02375 AC 14.10.01/5433
Embedding depth	30 mm
Depth	40 mm
Width	45 mm
Height	45 mm
Net weight	0.035 kg
Surface treatment	Untreated

Environment

Ambient air temperature for operation	1530 °C
Ambient air temperature for storage	035 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Acetone Alcohol Bleach Liquid soap Oil UV resistant Petrol

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	36.0 g
Package 1 Height	4.4 cm
Package 1 width	6.5 cm
Package 1 Length	6.8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	450.0 g
Package 2 Height	4.4 cm
Package 2 width	13.6 cm
Package 2 Length	33.5 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	2.26 kg
Package 3 Height	15.0 cm
Package 3 width	30.0 cm
Package 3 Length	40.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months

Warranty	18 months