

## LED FILAMENT CANDLE C35



### **Technical data**

<i>Rated voltage:</i>	230V; 50-60Hz
<i>Power:</i>	2W; 4W;
<i>Colour temperature:</i>	2700K;
<i>LED type:</i>	COB bracket
<i>LED source:</i>	Epistar Taiwan
<i>Lamp holder:</i>	E14
<i>Beam angle:</i>	360°
<i>Colour body:</i>	Mat
<i>Colour rendering index:</i>	Ra≥80
<i>Warm-up time (60 %):</i>	Instant
<i>Number of switching cycles:</i>	>20 000
<i>Average life:</i>	30 000h
<i>Power factor:</i>	$\lambda > 0.80$
<i>Starting time:</i>	< 0.50s
<i>Lamp mercury content:</i>	0.0mg


## Features

- o *Reduced operational cost thanks to lower energy consumption.*
- o *Lower maintenance cost thanks to longer lifetime*
- o *Mercury free.*
- o *Maximum resistance to switching loads.*
- o *Correct operation even at low temperature.*
- o *Instant-on light.*

## Area of application

- o *General illumination*
- o *Domestic applications*
- o *Chandeliers*
- o *Outdoor applications only in suitable luminaires*

## Variants and Dimensions




Watt	Whole fixture lumens	Colour temp.	Beam angle	Colour body	Size (mm)		Catalogue number
					Length	Diameter	
<b>2</b>	200	2700	360°	Mat	100	35	<b>99LED706</b>
<b>4</b>	400	2700	360°	Mat	100	35	<b>99LED662</b>

## Barcodes

3800131188717	99LED706
3800131187246	99LED662

## Energy efficiency



## Standards

- EN 55015 • EN 61000-3-2 • EN 61000-3-3 • EN 61547 • EN 13032-4 • EN 62560 •

