

# EL<sup>®</sup>MARK

The Brand of Electricity

## CABLE SUPPORT SYSTEM ACCESSORIES



### Self-extinguishing pliable conduits EC:



- Material: technopolymer on PVC base, Self-extinguishing V0 degree to UL94
- Compression resistance: 320N
- RAL 7035

Type	Inner Diameter Ø (mm)	Outer Diameter Ø (mm)	Packing (m)	Catalogue number
<b>Self-extinguishing pliable conduits</b>	10,7	16	100	500M16
	14,1	20	100	500M20
	18,2	25	50	500M25
	24,3	32	25	500M32
	32,3	40	25	500M40
<b>Self-extinguishing pliable conduits with draw tape</b>	10,7	16	100	500N16
	14,1	20	100	500N20
	18,2	25	50	500N25
	24,3	32	25	500N32
	32,3	40	25	500N40

### Spiral flexible PVC conduits- UV rays resistant EC:



- Material: (spiral + cover) – shock resistance technopolymer on PVC base
- Self-extinguishing V0 degree to UL94
- Compression resistance: 320N
- Installation temperature: -15° ÷ +70°
- Operating temperature: -5° ÷ +65°

# TECHNICAL SPECIFICATION

## CABLE SUPPORT SYSTEMS

**ELMARK**<sup>®</sup>

The Brand of Electricity

Type	Inner Diameter Ø (mm)	Outer Diameter Ø (mm)	Packing (m)	Catalogue number
<b>UV flexible PVC conduit</b>	12	16,2	30	500UV12
	14	18,2	30	500UV14
	16	20,2	30	500UV16
	20	24,2	30	500UV20
	25	29,6	30	500UV25
	32	37,2	30	500UV32

### Spiral for cables:



- Flexible, reusable, spiral design, polyethylene material
- It organizes and protects from possible damages all types of cables
- Can easily be cut off to the length you need
- Ideal for home and office use

Type	Colour	Internal diameter (mm)	External diameter (mm)	Coil length (mm)	Catalogue number
<b>Spiral 6x8mm</b>	transparent	6	8	25	500SP6T
<b>Spiral 6x8mm</b>	black	6	8	25	500SP6B
<b>Spiral 10x12mm</b>	transparent	10	12	25	500SP10T
<b>Spiral 10x12mm</b>	black	10	12	25	500SP10B
<b>Spiral 14x16mm</b>	transparent	14	16	20	500SP14T
<b>Spiral 14x16mm</b>	black	14	16	20	500SP14B

---

### Nylon cable draw tape EC:

---



- Draw tape with strong brass hooks
- Available in 5m and 15m lengths.
- Material: Nylon
- Used for pulling cables through conduit, ducting, trunking & through ceiling voids

Type	Diameter Ø (mm)	Length (m)	Colour	Packing (pcs)	Catalogue number
Nylon cable draw tape	3	5	Transparent	1/340	500305
	3	15	Transparent	1/120	500315

---

### PVC insulated steel spirals:

---



- Material: Galvanized steel, helically wound, flexible steel conduit with PVC coating; PVC – resistant against corrosion
- Colour – black
- Operating temperature: -5° ÷ +65°

# TECHNICAL SPECIFICATION

## CABLE SUPPORT SYSTEMS

**ELMARK**<sup>®</sup>

The Brand of Electricity

Type	Inner Diameter Ø (mm)	Outer Diameter Ø (mm)	Packing (m)	Catalogue number
<b>PVC insulated steel spirals</b>	11	15.2	50	500P11
	14	18.4	50	500P14
	16	20.4	50	500P16
	18	22,4	50	500P18
	26	30,4	25	500P26
	37	42,4	25	500P37

### PVC insulated steel spirals:



Rigid insulating conduit are practical solution of organizing power and communication cables in office and residential buildings. They increase the reliability in operation of the electrical systems. Fast and simple installation. In combination with a wide range of accessories, building irregularities are quickly overcome. Nonflammable material, easy to cut and paint.

- Material – shock resistance techno polymer on rigid PVC base
- Selfextinguishing V0 degree to UL94
- Compression resistance – 320N

Type	External diameter Ø (mm)	Length (m)	Colour	IP code	Packing (pcs)	Catalogue number
<b>Plastic cable conduit, with sleeve</b>	16	3	grey	IP40	34	50016
	20	3	grey	IP40	34	50020
	25	3	grey	IP40	20	50025
	32	3	grey	IP40	10	50032
	40	3	grey	IP40	10	50040

#### Standards:

EN 61386-1

EN 61386-21



[www.elmarkholding.eu](http://www.elmarkholding.eu)