

The Brand of Electricity

DOUBLE MALE SINGLE FEMALE CABLE COUPLER



Double male single famale/male cable coupler is compatible with MC4 connectors and is suitable with solar power cable H1Z2Z2-K with cross section 2.5mm2; 4mm2 and 6mm2.

- :. It does not need extra instruments for the removal of plugs
- :. Removal will not cause any harm to plugs.
- :. Load capablility with big current and high voltage
- :. Good ability of resistance and machine shocking
- :. Lower contact resistance

TECHNICAL SPECIFICATION

CABLE TERMINALS



TECHNICAL DATA »

∴ Rated voltage: 1000V∴ Rated current: 30A


∴ Test voltage: 6KV (50Hz)

∴ IP code: IP67

∴ Contact material: Copper, silver plated∴ Operating temperature: -40 to +125°C

:. Suitable cable cross section: 2.5mm2; 4mm2 and 6mm2

: Range of cable glands: 3-6mm



PRODUCT DETAILS »

Catalogue number	Туре	Range of cable glands (mm)	Conductor cross section (mm²)	IP code	Barcode	Packing
411080/M	2 male/ 1 female coupler	3-6	4/6	IP67	3800131234285	1
411080/F	2 female/ 1 male coupler	3-6	4/6	IP67	3800131234278	1

