50952 **Vigor LED Microwave Emergency**

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Gloss white & opal PC finish
- Constructed from polycarbonateComplete with built in microwave sensor
- 3 hours emergency maintained fitting
- Suitable for indoor or outdoor use
- Can be ceiling and wall mounted

SPEC DATA

Product Wattage:	16W & 2W(EM)
Product Lumen:	1200
Lumen/W:	75
Kelvin:	4000
Energy Rating:	A+
Dimmable:	No
Beam Angle:	120°
Power Factor:	0.9
CRI:	80
Lifetime (Hours):	35000
LED Brand:	Epistar
SDCM:	<6
Driver Type:	Constant Current
Product Voltage:	220-240V
Herts:	50/60
Surge Protection (KV):	1.5
Operating Temp:	-20 to 45 Degree
IP Rating:	65
IK Rating:	08
Product Weight (KG):	1.575
Terminal Block:	4-way fast fix
Class:	1

1000 +10 20°).9 30 35000 Epistar <6 Constant Current 380mA 220-240V 50/60 .5 20 to 45 Degree 65)8 .575 I-way fast fix

MICROWAVE MOVEMENT SENSOR DATA

Operating Voltage: Herts:	220 ~ 240Vac 50/60
Rated Load:	400W (Capacitive load) 800W (Resistive load)
Stand-by Power:	<0.5W
Sensitivity:	Ceiling Height 3m: 100% / 75% / 50% / 25% / 10%
	Ceiling Height 6m: 100% / 75% / 50%
	Wall Height 2m: 100% / 75% / 50% / 25% / 10%
Hold-time:	5s / 30s / 90s / 3min / 20min / 30min
Daylight Sensor:	2Lux / 10Lux / 25Lux / 50Lux / Disable
Microwave Frequency:	$5.8~\text{GHz}~\pm75\text{MHz}$
Transmitting Power:	1mW Max.
Detection Range:	Ceiling Height 3m: 3-6m (radius)
	Wall Height 1.5-2m: 12-15m
Detection Angle:	360° (Ceiling) / 120° (Wall)
Working Temperature:	$-20^{\circ}C \sim 60^{\circ}C$





