


Constant Voltage 24V LED Driver

Features:

- Independent compact design
- Protections: opencircuit, shortcircuit, overload, overtemperature
- Simple installation
- SELV equivalent
- Protection class II
- Non-Dimmable



Parameters:

Model No.	Input voltage (V)	Output voltage (V)	Output current (A)	Power factor (λ)	Ambient temperature ta (°C)	Max. casing temperature tc (°C)	Type of light source for which it is intended	Efficiency full load (%)	No-load power (Pno in W)	Standby power (Psb in W)	Suit for dimming (Y/N)	Networked standby power (Pnet in W)	For OLED and HL Maximum output power (W)	Max. output (W)	Dimensions LxWxH (mm)	Weight (g)
79682	220-240	24	0-0.83	0.80	-20...+50	80	LED	83	N/A	N/A	N	N/A	N/A	20	113x44x28	100
79328	220-240	24	0-1.7	0.95	-20...+50	85	LED	86	N/A	N/A	N	N/A	N/A	40	166x52x24	140
79329	220-240	24	0-0.31	0.95	-20...+50	85	LED	89	N/A	N/A	N	N/A	N/A	75	184x61x32	270
79681	220-240	24	0-6.25	0.95	-20...+45	85	LED	91	N/A	N/A	N	N/A	N/A	150	210x67x34	320
98992	220-240	24	0-0.25	0.55C	-20...+50	80	LED	78	N/A	N/A	N	N/A	N/A	6	81x39x22	50
98993	220-240	24	0-0.50	0.80C	-20...+50	80	LED	82	N/A	N/A	N	N/A	N/A	12	98x39x22	100
98994	220-240	24	0-2.1	0.95	-20...+50	85	LED	87	N/A	N/A	N	N/A	N/A	50	184x61x32	270
98995	220-240	24	0-2.5	0.95	-20...+50	85	LED	89	N/A	N/A	N	N/A	N/A	60	184x61x32	270
98996	220-240	24	0-4.2	0.95	-20...+50	85	LED	92	N/A	N/A	N	N/A	N/A	100	184x61x32	300