



Constant Voltage TRIAC Dimming LED Driver

Features:

- Dimmable with leading edge or trailing edge dimmer
- Independent compact design
- Protections: opencircuit, shortcircuit, overload, overtemperature
- SELV equivalent
- Protection class II
- Smooth dimmable compatible with most dimmer
- Dimming range 1...100%



Parameters:

Model No.	Input voltage (V)	Output voltage (V)	Output current (A)	Power factor (λ)	Ambient temperature ta (°C)	Max. casing temperature tc (°C)	Type of light source for which it is intended	Efficiency full load (%)	No-load power (Pno in W)	Standby power (Psb in W)	Suit for dimming (Y/N)	Networked standby power (Pnet in W)	For OLED and HL Maximum output power (W)	Max. output (W)	Dimensions LxWxH (mm)	Weight (g)
79332	220-240	24	0.1-1.04	0.95	-20...+50	70	LED	85	N/A	N/A	Y	N/A	N/A	25	128x52x30	110
79333	220-240	24	0.5-2.08	0.95	-20...+50	70	LED	86	N/A	N/A	Y	N/A	N/A	50	184x61x32	240
79334	220-240	24	1.4-4.2	0.95	-20...+45	80	LED	91	N/A	N/A	Y	N/A	N/A	100	210x67x34	360