

72180

Luik Microwave Gear Tray

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Complete with built in microwave sensor

SPEC DATA

Product Wattage:	18W
Product Lumen:	2150
Lumen/W:	119
Kelvin:	4000K
Energy Rating:	A+
Dimmable:	No
Beam Angle:	120°
Power Factor:	0.9
CRI:	80
Lifetime (Hours):	35000
LED Brand:	Epistar
SDCM:	<6
Driver Type:	Constant Current 380mA
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 45 Degree
Product Weight (KG):	0.5
Terminal Block:	3-way fast fix
Class:	1
Product Lumen with Plain Casing:	1210Lm
EM Wattage / Lumen with Plain Casing:	2W / 200Lm
Product Lumen with Eyelid Casing:	770Lm
Product Lumen with Grill Casing:	1010Lm

MICROWAVE MOVEMENT SENSOR DATA

Operating Voltage:	220 ~ 240Vac
Hertz:	50/60
Rated Load:	400W (Capacitive load) 800W (Resistive load)
Stand-by Power:	≤ 0.5W
Sensitivity:	Ceiling Height 3m: 100% / 75% / 50% / 25% / 10% Ceiling Height 6m: 100% / 75% / 50% Wall Height 2m: 100% / 75% / 50% / 25% / 10%
Hold-time:	5s / 30s / 90s / 3min / 20min / 30min
Daylight Sensor:	2Lux / 10Lux / 25Lux / 50Lux / Disable
Microwave Frequency:	5.8 GHz ± 75MHz
Transmitting Power:	1mW Max.
Detection Range:	Ceiling Height 3m: 3-6m (radius) Wall Height 1.5-2m: 12-15m
Detection Angle:	360° (Ceiling) / 120° (Wall)
Working Temperature:	-20°C ~ 60°C

