

# Product data sheet

Specifications



Socket-outlet, New Unica, mechanism, 2P + E, 16A, French, shutter, screwless terminals, IP3x, glossy, antibacterial, red

NU304903T

## Main

Range	New Unica
Product or component type	Socket-outlet
Device presentation	Mechanism
Device mounting	Flush
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	French
Outlet standard description	Pin earth
Ground lug position	45° ground lug
Rated current	16 A

## Complementary

Device application	Power supply
Cover type	With shutter
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Red (Pantone 1795C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible 0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover
Surface finish	Glossy

<b>Quantity per set</b>	Set of 1 without packaging
<b>Standards</b>	IEC 60884-1 NF C 61-314
<b>Product certifications</b>	NF
<b>Embedding depth</b>	28.4 mm
<b>Depth</b>	37.7 mm
<b>Width</b>	45 mm
<b>Height</b>	45 mm
<b>Net weight</b>	0.031 kg
<b>Surface treatment</b>	Antibacterial
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	-5...35 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP3x
<b>Environmental characteristic</b>	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.8 cm
<b>Package 1 Width</b>	4.5 cm
<b>Package 1 Length</b>	4.5 cm
<b>Package 1 Weight</b>	31.0 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	5.5 cm
<b>Package 2 Width</b>	10.0 cm
<b>Package 2 Length</b>	27.0 cm
<b>Package 2 Weight</b>	393.0 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	140
<b>Package 3 Height</b>	30.0 cm

<b>Package 3 Width</b>	30.0 cm
<b>Package 3 Length</b>	40.0 cm
<b>Package 3 Weight</b>	5.944 kg

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant with Exemptions
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Circularity Profile</b>	No need of specific recycling operations
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Minimum percentage of recycled plastic content</b>	65

## Recommended replacement(s)