

Product data sheet

Specifications



2 Socket-outlet, New Unica, mechanism, 2P + E, 16A, French, with shutter, screwless terminals, IP3x, glossy, white

NU306918SE

Main

| | |
|-----------------------------|----------------|
| Range | New Unica |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism |
| Device mounting | Flush |
| Socket number | 2 |
| Outlet poles configuration | 2P + E |
| Outlet standard | French |
| Outlet standard description | Pin earth |
| Ground lug position | 45° ground lug |
| Rated current | 16 A |

Complementary

| | |
|--------------------------------|---|
| Device application | Power supply |
| Cover type | With shutter |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Number of modules | 4 modules |
| Fixing mode | Clip-in |
| Colour tint | White (RAL 9003) |
| Pilot light | Red indicator lamp, colour: red, current consumption: 1.5 mA |
| Connections - terminals | Screwless terminals |
| Cable cross section | 0...2.5 mm ² cable(s), 2 - cable stiffness: flexible 0...2.5 mm ² cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover |

| | |
|-------------------------------|---|
| Surface finish | Glossy |
| Quantity per set | Set of 1 without packaging |
| Standards | IEC 60884-1 NF C 61-314 |
| Product certifications | NF |
| Embedding depth | 30 mm |
| Depth | 39.4 mm |
| Width | 45 mm |
| Height | 90 mm |
| Net weight | 0.077 kg |
| Surface treatment | Untreated |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -5...35 °C |
| Ambient air temperature for storage | -5...50 °C |
| IK degree of protection | IK04 |
| IP degree of protection | IP3x |
| Environmental characteristic | Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4 cm |
| Package 1 Width | 4.5 cm |
| Package 1 Length | 9 cm |
| Package 1 Weight | 73 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 5 |
| Package 2 Height | 12.8 cm |
| Package 2 Width | 12.3 cm |
| Package 2 Length | 18.5 cm |
| Package 2 Weight | 430 g |
| Unit Type of Package 3 | S02 |
| Number of Units in Package 3 | 20 |

| | |
|-------------------------|----------|
| Package 3 Height | 15 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 2.035 kg |

Offer Sustainability

| | |
|---|--|
| EU RoHS Directive | Under investigation |
| Circularity Profile | No need of specific recycling operations |
| Minimum percentage of recycled plastic content | 59 |

Recommended replacement(s)